



# PM454 Pager Module Specification Sheet

IL848  
Section C  
Rev. 0 - 09/2007



### FEATURES

The PM454 Pager Module has an isolated RS232 serial port designated for a compatible paging transmitter. The port is isolated to help shield the NC450 Central Equipment from externally induced damage and to help prevent external voltage differentials from affecting the nurse call system.

### SPECIFICATIONS

Dimensions:    Height: 10.6" (269 mm)  
                         Width: 2.376" (60 mm)  
                         Depth: 4.082" (104 mm)

Temperature: 0°-70°C.  
Humidity: 5-95% (non-condensing)

### ARCHITECTS' AND ENGINEERS' SPECIFICATION

Pager Module shall be TekTone®'s PM454 or approved equal. The module shall include an RS232 serial port designated for a compatible paging transmitter. Port shall be isolated.

The PM454 shall be UL® 1069 Listed and cUL® Listed.

### REQUIRED COMPONENTS

Tek-CARE®400 Nurse Call System  
NC450 Central Equipment  
NC365A Tek-PAGING™ Transmitter/Control Unit  
NC397A Alphanumeric Pager

[www.tektone.NET](http://www.tektone.NET)

277 Industrial Park Road • Franklin, NC 28734 • Phone (828) 524-9967 • Fax (828) 524-9968

Email: [tektone@tektone.net](mailto:tektone@tektone.net) • Technical Assistance Email: [teksupt@tektone.net](mailto:teksupt@tektone.net)

**TekTone®'s quality system is registered by UL® to the ISO 9001:2000 standard. (File #A10766.)**