



**Area of Refuge  
Systems**

# AlphaRefuge™

## 2400 Series

**The ADA Compliant Solution for Buildings with up to 112 Remote Call Boxes**



**Meets all requirements of IBC, ADA, ASME and NFPA**



Proudly Made  
in the U.S.A.

AL026 - Rev 4 (05/2017)

## REFUGE COMMAND CENTERS (Masters)



### ◀ Choose from the following Enclosed Cabinet Masters\*:

#### **RCC2516CS - 16 Remote Max Surface Command Center**

O.D. : 14.73"W X 11.87"H X 6.125"D (mm: 375 W X 302 H X 156 D)

#### **RCC2516CF - 16 Remote Max Flush Command Center**

O.D. : 14.00"W X 16.11"H X 3.00"D (mm: 356 W X 410 H X 77 D)

#### **RCC2556CS - 56 Remote Max Surface Command Center**

O.D. : 25.00"W X 21.11"H X 5.125"D (mm: 635 W X 537 H X 131 D)

#### **RCC2556CF - 56 Remote Max Flush Command Center**

O.D. : 23.00"W X 20.64"H X 3.00"D (mm: 585 W X 525 H X 77 D)

#### **RCC25112CS - 112 Remote Max Surface Command Center**

O.D. : 25.00"W X 21.11"H X 5.125"D (mm: 635 W X 537 H X 131 D)

#### **RCC25112CF - 112 Remote Max Flush Command Center**

O.D. : 23.00"W X 20.64"H X 3.00"D (mm: 585 W X 525 H X 77 D)

\* All model numbers above include the required PBX equipment



### ◀ **PWRAPC**

#### **Remote PBX Power Supply**

O.D. : 3.90"W X 9.80"H X 15.00"D (mm: 100 W X 249 H X 381 D)

1 Per System for Remote Power (Up to 36 Remote PBX Call Boxes)

#### **PWRAPC112**

#### **Remote PBX Power Supply**

O.D. : 7.70"W X 17.00"H X 21.45"D (mm: 196 W x 432 H x 545 D)

1 Per System for Remote Power (Up to 112 Remote PBX Call Boxes)

## Standard Features

- Battery Backup which provides up to 3 hours of full operation.
- Two number programming.
- Operating Temperature of between -40°F to +150°F (-40° to + 65° C)
- On-Site Programmable.
- EEPROM memory to protect programming
- Coordinates and controls in-building rescue in the event of an emergency.
- Audible alert sounds when Refuge Call Boxes place call until Command Center joins conversation.
- LEDs indicate which Refuge Call Box(es) initiated a call and eliminate the guesswork for emergency personnel.
- Rescue personnel pick up the Command Center handset and communicate with Refuge Call Box and any existing off-site emergency calls
- Install Refuge Command Center in a central location on the first floor or in an area approved by the local authority having jurisdiction (AHJ)
- IBC, NFPA and ADAAG Code Compliant

## REFUGE CALL BOXES (Remotes)



**RCB2400R**

**Red Powder Coat  
Finished Surface  
PBX Call Box**

O.D. : 5.125"W X 8.125"H X 2.125"D  
(mm: 131 W X 207 H X 54 D)



**RCB2400RN**

**Red Fiberglass NEMA 4 Rated  
Outdoor Surface PBX Call Box**

O.D. : 5.25"W X 8.25"H X 2.75"D  
(mm: 134 W X 210 H X 70 D)



**RCB2400RNCOV**

**Red Fiberglass NEMA 4 Rated  
Outdoor Surface PBX Call Box  
with Protective Cover**

O.D. : 6.60"W X 9.90"H X 3.25"D  
(mm: 168 W X 251 H X 83 D)  
Cover: 3.75"W X 6.40"H X 2.25"D  
(mm: 95W X 163 H X 57.15 D)



**RCB2400SF**

**Brushed Stainless  
Steel Flush PBX  
Call Box**

O.D. : 9.75"W X 12.50"H X .50"D  
(mm: 248 W X 318 H X 13 D)  
I.D. : 6.00"W X 8.25"H X 3.00"D  
(mm: 153 W X 210 H X 77 D)



**RCB2400SFCOV**

**Brushed Stainless  
Steel Flush PBX  
Call Box w/ Cover**

O.D. : 8.00"W X 11.375"H X 2.00"D  
(mm: 203 W x 289 H x 51 D)  
I.D. : 6.50"W X 8.875"H X 3.00"D  
(mm: 165 W x 225 H x 76 D)  
Cover : 6.125"W X 9.90"H X 1.75"D  
(mm: 156 W x 251 H x 44 D)



**RCB2400S**

**Brushed Stainless  
Steel Surface PBX  
Call Box**

O.D. : 5.125"W X 8.125"H X 2.125"D  
(mm: 131 W X 207 H X 54 D)



**RCB2400SRCOV**

**Brushed Stainless Steel Surface  
Call Box With Protective Cover**

Face Plate: 6.70"W X 10.00"H  
(mm: 170 W x 254 H)  
BackBox: 6.50"W X 9.875"H X 2.30"D  
(mm: 165 W x 251 H x 58 D)  
Cover : 6.125"W X 9.90"H X 1.75"D  
(mm: 156 W x 251 H x 44 D)



*Proudly Made  
in the U.S.A.*

**NOTE:** Some models also available with mushroom-head buttons. Please contact us for more information.





# Area of Refuge AlphaRefuge™ Signage



Proudly Made  
in the U.S.A.



**Blue Wall Signs w/ Arrow**  
RSN7047R: Right Arrow  
RSN7047L: Left Arrow  
15.0"W X 5.0"H



Depending on the size of the building, an AHJ may require direction signage to get the occupants to the location.

## Photoluminescent Wall Sign

RSN7041  
8.00"W X 8.00"H X 0.25"D



**Blue Wall Signs w/ Braille**  
RSN7044  
6.0"W X 9.0"H



RSN7087  
8.0"W X 8.0"H

Tactile signage or raised letter & braille signage is required at the entrance of the area of refuge to designate the area as such.

**Red Lighted Refuge Sign**  
RSN7050 - 120VAC  
14.0" W x 10.5" H x 3.00" D  
Includes Battery Backup



**White Wall Sign w/ Braille**  
RSN7043  
6.0"W X 9.0"H

**Photoluminescent Wall Sign w/ Braille**  
RSN7046  
8.00"W X 8.00"H X 0.25"D



Some AHJs will accept this sign to take the place of the RSN7041 and RSN7044 so you only need one of these at the entrance to the area of refuge.



**Instruction Sign w/ Braille**  
RSN7049  
6.0"W X 8.0"H

**Self-Stick Floor Decal**  
RSN7045  
17.0" Diameter

A large floor decal is typically not required, but it makes locating an Area of Refuge much easier, especially for people with impaired vision, or in limited sight situations.



42 Central Drive - Farmingdale NY 11735-1202  
Phone: 631-777-5500 Fax: 631-777-5599  
TOLL-FREE: 800-666-4800  
www.AlphaCommunications.com

Available From: