



Product Specification Sheet



APS021
Rev. 8 - 03/20011



SF301/8



SF302
SF302/10

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The call cord(s) shall be Alpha Communications® Model SF301/8 (single) or SF302 (double) or approved equal. Model SF301/8 shall provide for a single momentary call button. Model SF302 shall provide a 'Y' type cord with two momentary call buttons. The call cords shall be made to U.L.® 1069 standards and encased in a molded, shock-proof plastic case. The SF301/8 shall be (shall be ETL Listed) and shall be provided with an 8' polyvinyl cord and the SF301/10 shall be provided with a 10' polyvinyl cord. The SF302 shall be provided with dual 6' polyvinyl cords and the SF302/10 shall be provided with dual 10' polyvinyl cords. Call cords shall include the HW155 security "bed" clip attached, and shall feature a right-angle molded plug assembly. Call cords shall be able to withstand gas sterilization without damage, but should not be used in oxygen-rich environments. (except for the newest model SF301/8).

Copyright© 1997-2011, Alpha Communications®, All Rights Reserved

SF301/8 and SF302 Series Call Cords

The Alpha Communications® SF301/8 (single) or SF302 (double) call cords are specifically designed to be used with the NC110A, NC110N, NC150N, NC200N, NC205, NC300 and NC300II Nurse-Call Systems, and on NC500 Emergency-Call systems, on bed stations utilizing 1/4" type phono jacks.

The SF301/8 cord features an 8 foot long cord, and the SF302 features twin 6 foot cord lengths. A wide variety of optional call cords are also available for specialty applications such as geriatric use, and air-call. Ten foot cords are also available in single (SF301/10) and double (SF302/10) cord styles. Other length cords are available on special-order.

FEATURES

- Simple push button operation and "winged" pendant
- Made to U.L.® 1069 or ETL specifications
- S.P.S.T. 1-Amp Momentary Switch
- Integral brass, hard gold contacts
- Rugged and Reliable. Can be gas sterilized
- Dirt and dust protection
- Small, lightweight pendant fits comfortably in hand
- Bed sheet clips included
- 500 mA, 50-watt maximum, AC
- ESD protection to 15,000 volts
- SAFE FOR USE IN OXYGEN ENVIRONMENTS (newest version ETL Listed model SF301/8 ONLY!!)

SPECIFICATIONS

Construction: Cord shall be made from a heavy duty polyvinyl covered cord with molded right-angle plug and momentary contact button encased in a shockproof plastic "winged" pendant.

Push Button: Momentary S.P.S.T. type with integral brass, hard gold contacts, molded into a comfortable "winged" hand pendant.

CALL CORD OPERATION

The patient, by pressing the momentary button on the SF301/8 (or other equivalent SF301 and/or SF302 series) call cord shall signal for assistance. The actual call signaling functions depend upon which system the call cord is being used.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.