



**IR345C Master  
Occupant HELP Station (OHS)**

## ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The master (main) occupant help station(s) (OHS) shall be Alpha Communications®/Tektone IR345C or approved equal. The IR345C shall include solid-state LSI/microprocessor technology, a red "CALL" indicator, a 6' long pull cord for "HELP" call placement, a routine "CALL" push button and a "CHECK-IN/RESET" push button.

All station components shall be housed in an attractive, flame retardant type ABS plastic panel. Plug-in type connectors shall be used for electrical connections.

Contractor shall observe all local and national electrical and building codes.

Tek-Check-In™ is a registered trademark of Tektone Sound & signal Mfg. Inc.

Copyright© 1997-2004, Alpha Communications®, All Rights Reserved

## IR345C Occupant Help Station

The IR345C Occupant Help Station is for use with Alpha Communications® HC345C Tek-Check-In™ System. It provides emergency signaling and reliable two-way, hands-free communication between the resident/patient and the staff member at the system master station(s). Stations may be programmed for privacy, paging and patient priority from the master station.

Calling the master station is accomplished either by pulling the 6' long "HELP" cord mounted on the panel or by depressing the routine "CALL" button. Call-placed assurance is indicated by the red indicator. The speaker-microphone is sensitive enough to assure clear conversation even with weak resident/patient inputs. Calls are canceled simply by depressing the "RESET" button.

Check-in at the master station is accomplished by depressing the "CHECK-IN" push button mounted on the station. This removes the resident's apartment number from the "NCI" (not-checked-in) column on the master station video monitor (NC313 with NC314A).

### FEATURES

- Emergency calling with "HELP" indication at the master station.
- Push button routine "CALL" and "CHECK-IN" operation
- Solid-state LSI/microprocessor controlled design.
- Attractive, flame retardant type ABS white plastic faceplate.

### SPECIFICATIONS

<b><u>Dimensions:</u></b>	Height: 5.50" (114mm)
	Width: 6.38" (162mm)
	Depth: 2.88" (73mm)
	Projects: 0.38" (9.5mm)
<b><u>Construction:</u></b>	Attractive, flame retardant type ABS plastic (white).
<b><u>Speaker:</u></b>	2.50" diameter, 60 ohm w/voice response
<b><u>Connections:</u></b>	Plug-in connectors
<b><u>Housing:</u></b>	Alpha Communications® IH353 box with IH352 ring (or Steel City #H3BD with Steel City #3GC plaster ring), or EXACT EQUAL. Horizontal mount.

### REQUIRED COMPONENTS

<b><u>HC345C</u></b>	Central Processing Equipment (CPE)
<b><u>NC313</u></b>	Video Monitor(s) with <b><u>NC314A</u></b> adaptor(s)
<b><u>NC303</u></b>	Master Station(s)

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*