



**IR145B Remote
Occupant HELP Station (OHS)**

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The remote occupant help station(s) (OHS) shall be Alpha Communications®/Tektone IR145B or approved equal. The IR145B shall include solid-state LSI/microprocessor technology, a red "CALL" indicator and a 6' long pull cord for "HELP" call placement. IR145B stations must be used in conjunction with the IR345C (main) occupant help stations (OHS).

All station components shall be housed in an attractive, flame retardant type ABS plastic panel. Plug-in type connectors shall be used for electrical connections.

Contractor shall observe all local and national electrical and building codes.

Tek-Check-In™ is a registered trademark of Tektone Sound & Signal Mfg. Inc.

Copyright© 1997-2004, Alpha Communications®, All Rights Reserved

IR145B Occupant Help Station

The IR145B Remote Station is for use with Alpha Communications®'s HC345C Tek-Check-In™ system. It provides emergency signaling and reliable two-way, hands-free communication between the resident/patient and the staff member at the system master station.

Calling the master station is accomplished by pulling the 6' long "HELP" call cord mounted on the panel. Call-placed assurance is indicated by the red "CALL" indicator. The speaker-microphone is sensitive enough to assure clear conversation even with weak resident/patient inputs. Calls are canceled simply by returning the reset switch to the "LEFT" position.

FEATURES

- UL1069 Listed - 4th Edition Standards
- Simple and flexible operation
- "Call-Placed" indicator
- Call cancel at point of origin
- Flame retardant type ABS (white) plastic faceplate
- 1.5" wide, Pull-Down lever

SPECIFICATIONS

Dimensions:	Height: 5.50" (114mm)
	Width: 6.38" (162mm)
	Depth: 2.88" (73mm)
	Projects: 0.38" (9.5mm)
Construction:	Attractive, flame retardant type ABS plastic (white)
Speaker:	2.50" diameter, 60 ohm w/voice response
Connections:	Plug-in connector
Housing:	Alpha Communications® IH353 box with IH352 ring or Steel City #H3BD with Steel City #3GC plaster ring, or EXACT EQUAL. Horizontal mount.

REQUIRED COMPONENTS

HC345C	Central Processing Equipment
NC313	Video Monitor(s) with NC314A adaptor(s)
NC303	Master Station
IR345C	Occupant Help Station w/intercom, emergency signaling capability, and check-in button

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.