



**PK601A DC Power Supply**

### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The power supply shall be Alpha Communications®/Tektone model PK601A or approved equal and shall provide 24 volts DC power to auxiliary signaling devices used in specified Alpha Communications® emergency-call or other systems.

The PK601A shall be suitable for use as a DC silent door opener adaptor in specified Alpha Communications® apartment entrance systems.

The PK601A circuitry shall be housed in a rugged extruded aluminum case. Positive screw terminals shall be provided for installing wiring.

Contractor shall observe all local and national electrical and building codes.

### PK601A DC Power Supply

The PK601A is a 24VDC power supply used to power auxiliary signaling devices, typically used in Alpha Communications® emergency-call systems. The unit provides a filtered 24 volt DC output rated at 1 amp.

Although specifically designed for use with emergency-call systems, the PK601A may also be used as a DC silent door opener adaptor in Alpha Communications® apartment entrance systems, as well as a DC power source for other systems.

The PK601A is powered by our model SS106 (or equivalent) transformer.

### FEATURES

- Easy installation
- Low-voltage operation
- Multiple applications
- Precision engineering

### SPECIFICATIONS

**Dimensions:** Height: 5.00" (127mm)  
Width: 2.38" (60mm)  
Depth: 2.25" (57mm)

**Construction:** Rugged extruded aluminum case, housing quality electronic components on a printed circuit board.

**Connections:** Positive screw terminals

**Mounting:** Surface

**Power Required:** 24 volts DC

**Duty:** Light  
**Load Current:** 1 amp

**Power Requirements:** 16VAC, 30VA

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*