



**SF333**

### **ARCHITECTS' AND ENGINEERS' SPECIFICATIONS**

Patient emergency station shall be Alpha Communications®/Tektone SF333 or approved equivalent. Operation of all emergency signals shall be accomplished by depressing the centrally located push button designated "EMERGENCY". The red "Call-Placed" indicator shall flash to assure the patient that the call has been properly placed. The initiation of the emergency call shall cause the activation of both audible and visual signals. Call cancellation shall be possible only at point of origination. Reliable, solid state components shall be used and a plug-in connector shall be provided for electrical connections.

The SF333 shall be UL 1069 listed to the latest 4th Edition Standards. Contractor shall observe all local and national electrical and building codes.

Copyright© 1997-2009, Alpha Communications®, All Rights Reserved

### **SF333 Patient Emergency Station**

For use in toilets or similar areas where emergency call initiation may be required, the SF333 Patient Emergency station is used to operate all system emergency signals. A call is placed by depressing the centrally-located push button. The "Call-Placed" indicator flashes to provide for patient call assurance. Calls are registered on the master station (and duty station if used) via audible and visual signals. Call cancellation is possible only at the originating location.

The SF333 is typically used with the HC345C, NC205, NC300 and NC300II systems. The SF333 is not designed for use in a shower or 'moist' environment.

### **FEATURES**

- UL 1069 Listed - 4th Edition Standards
- Push button activation of "EMERGENCY" call
- Registers audible and visual calls at master station
- Indicates local call originating on dome lights
- Calls can be canceled only at point of origin
- Mounted on stainless steel faceplate

### **SPECIFICATIONS**

<b><u>Dimensions:</u></b>	Height: 4.50" (114mm) Width: 2.75" (70mm) Depth: 1.63" (29mm) Projects: 0.38" (10mm) from mounting surface
<b><u>Construction:</u></b>	Reliable components mounted on a rugged stainless steel faceplate
<b><u>Construction:</u></b>	Plug-in connectors
<b><u>Housing:</u></b>	Steel City #52171 box with Steel City #52C14 plaster ring, or Alpha Communications® Model #IH358 box with IH357 ring, or EXACTEQUAL. Vertical mount.

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*