



Product Specification Sheet



APS133

Rev. 3 - 04/2001



LI387 Corridor Light



LI389 Corridor Light

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

Corridor dome light(s) shall be Alpha Communications®/ Tektone model LI387 or LI389 or approved equivalent. The LI387 corridor dome light(s) shall be sectional in design and include a RED, GREEN, and BLUE translucent flame retardant polycarbonate translucent plastic lens; and a WHITE translucent flame retardant polystyrene plastic lens. The LI389 corridor dome light(s) shall be sectional in design and include two (2) RED, one (1) GREEN, and one (1) WHITE translucent flame retardant polystyrene plastic lens. All lenses shall be individually removable without the use of tools for ease of bulb replacement. All lenses shall be mounted on a fog-white flame retardant ABS plastic base panel. The lenses shall be individually removable without the use of any tools, for ease of bulb replacement. The use of separate bulbs to illuminate separate lenses of various colors shall provide clear indication of patient call priority and staff presence.

The LI387 and LI389 shall be U.L. 1069 Listed to the latest 4th Edition Standards. Contractor shall observe all local and national electrical codes.

LI387 / LI389 Corridor Lights

The Alpha Communications® LI387 and LI389 Corridor Light are sectional in design and is for use with the Alpha Communications® NC205 Nurse Call System. The LI387 and LI389 provide visual indication of calls originating from patient, staff, duty, staff presence, and code call stations. When used with patient or staff stations, the LI387 and LI389 will indicate all calls originated from that room. When used with a duty station, the LI387 and LI389 may be used as a zone light to indicate all calls from zones to which those stations are assigned. The LI387 and LI389 are normally used with Enhanced type remote and room stations.

FEATURES

- Easy bulb replacement without the use of tools
- Snap in colored lenses
- Excellent visibility
- Interchangeable lenses
- Provides zone light indications when used with a duty station

SPECIFICATIONS

Dimensions: Height: 4.56" (115mm)
 Width: 4.56" (115mm)
 Depth: 3.00" (76mm)
Bulbs: Model #LI028 28V, 70mA

Power

Requirement: 24VDC, 51mA (per bulb)

Finish: Base: FOG WHITE flame retardant ABS plastic

LI387 Lenses: Flame retardant translucent polycarbonate plastic (RED, GREEN, BLUE). Flame retardant translucent polystyrene plastic (WHITE). **LI389 Lenses:** same materials as LI387, except it has two (2) RED, one (1) GREEN and one (1) WHITE lens.

Mounting: Steel City #H2BD box with Steel City #2GC plaster ring, or Alpha Communications® Model #IH356 box with IH355 ring, or EXACTEQUAL.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.