



TA292A
(shown less coiled cord)

**ARCHITECTS' AND ENGINEERS'
SPECIFICATIONS**

The telephone handset intercom station shall be Alpha Communications®/Tektone model TA292A or approved equivalent and shall be molded of durable, high-impact ABS (white) plastic. Dynamic speech elements shall be used.

The phone shall be able to mount on a standard, single gang electrical box (or plaster ring) and shall have screw terminals for wiring hookup. A button shall be provided for door lock release. The TA292A shall require one (1) common and one (1) selective wire, to perform intercom and door opening functions. Signaling to handset shall be done with a pleasant electronic tone signal.

Contractor shall furnish and install the model PK292A system amplifier and any related components as required for proper system operation.

Contractor shall install as per manufacturers instructions and shall observe all local and national electrical codes.

**TA292A 2-Wire Telephone
Handset Intercom Station**

The Alpha Communications® TA292A handset telephone is designed especially for intercom use and features compact modern styling and advanced electronic design using dynamic speech elements and a reliable hook cradle switch. The TA292A is molded of high-impact flame retardant type ABS plastic and suitable for a variety of applications. The TA292A requires only one (1) common and one (1) selective wire per handset.

The TA292A easily mounts right on the surface of the wall, or over a single gang electrical back box or plaster ring.

FEATURES

- Clear, true voice reproduction
- Easy to install and use (requires only 2 wires)
- Pleasant Audio Tone Signal
- Built-In Door Release Button

SPECIFICATIONS

| | |
|--------------------------------|---|
| <u>Dimensions:</u> | Height: 8.50" (216mm) (not including cord) Width: 3.50" (89mm) Depth: 3.25" (82mm) |
| <u>Construction:</u> | High impact flame retardant type ABS Plastic (white) |
| <u>Speech Elements:</u> | Dynamic type with voice response |
| <u>Push Button:</u> | Replaceable type with plated, self-wiping contacts (for DOOR release function) |
| <u>Connections:</u> | Positive screw terminals |
| <u>Mounting:</u> | Standard single gang electrical box or plaster ring |

Do to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.