



PK410D

### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The door release adaptor shall be Alpha Communications®/Tektone PK410D or approved equal and shall provide for talk-controlled door release when used in conjunction with Alpha Communications® amplifier model IS543 and apartment station model IS204 or IS543 (or equivalent).

The adaptor shall have rugged construction and feature integrated circuit technology. Positive screw terminals shall be for installation wiring. Contractor shall observe all local and national electrical and building codes.

### PK410D Talk-Controlled Door Release Adaptor

The Alpha Communications® PK410D adaptor prevents tenants from opening the door without first activating the 'TALK' circuit. Before the door can be opened, the talk button on the intercom must be pushed; then conversation can be completed before opening the door.

After the talk button is pushed, the tenant has a 30-second time limit to open the door. The PK410D is designed for use with the IA543 amplifier and IS204 or IS543 (or equivalent type) apartment room stations.

### FEATURES

- Integrated circuit technology
- Low power requirements
- Easy installation

### SPECIFICATIONS

**Dimensions:** Length: 4.75" (120mm)  
Width: 2.38" (60mm)  
Depth: 2.25" (57mm)

**Construction:** High-quality electronic components mounted on a printed circuit board and housed in a rugged extruded aluminum case.

**Power Required:** 16 VAC, 10 VA.

**Mounting:** Surface-mounted

**Connections:** Positive screw terminals

*Do to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*