




Product Specification Sheet



APS154

Rev. 1 - 07/1998



SM404



SM406



SM411

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The master station(s) shall be Alpha Communications®/Tek-tone (SM404, SM406 or SM411) equipped with momentary-action push buttons for TALK, CALL, and DOOR operation. Each push button will have English or symbol function label. The PRIVACY and STATION selection function shall be controlled by a latching push button. MUSIC and VOICE shall be individually adjustable by means of a sliding control; accessible from the front face of the unit.

Dip switches shall be provided to selectively enable or disable call tone, all-call reception, selector LED time-out, CALL pre-announce tone, ALL-CALL pre-announce tone as well as call-tone type selection - either chime or buzz tone.

The station shall be molded of high-impact ABS plastic and have connections provided by plug-in pigtail connectors, which shall be supplied with the unit.

SM404 / SM406 / SM411 Master Stations

The SM404, SM406 and SM411 series master stations combine modern styling with ease of voice operation to provide natural, clear voice communication along with positive door release operation. Each button has labels or symbols explaining its function. Advanced circuitry and versatility permit the unit to call other units in the system as well as receive calls from other masters.

A wide variety of optional accessories is available to provide additional system functions such as ALL-CALL, system IN-USE indication, as well as door release activation of up to three separate door releases.

FEATURES

- Simple push button operation
- Easy Installation
- Advanced design
- Selectable privacy
- Clear voice fidelity
- Precision engineering
- All-call (paging) (optional)
- Background music available (optional)

SPECIFICATIONS

Dimensions:	Height: 7.13" (181mm) Width: 9.25" (235mm) Depth: 2.00" (50mm)
Finish:	Durable, high-impact, flame-retardant, fog white ABS plastic
Controls:	Individually replaceable push buttons identified with word or symbols
Speaker/Mic:	4x6 (101x152mm) with voice response. Also used to provide CALL and PAGE annunciation
Connections:	Plug-in pigtails with 11 conductors (3x)
Housings:	IH110R (flush) or IH401 (desk/surface)

TYPICAL REQUIRED COMPONENTS

PK400	Power Supply (1 per system)
SS106	Transformer (1 per PK400)
IR/OR Series	Remote Station(s) (if needed)
SM401	1-Call Master Station(s)

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.