



DPS-2

**ARCHITECTS' AND ENGINEERS'
SPECIFICATIONS**

The multi-entrance video adaptor(s) shall be Alpha Communications®/S.T.R.™ model DPS-2 (aka European model# TUV2), or approved equal. Unit(s) shall provide the control and power circuits needed to switch the video functions, to the calling entrance station camera location. Unit(s) shall be used in addition to standard system amplifier. Low voltage wiring shall be used and positive screw terminals shall be provided for installation wiring. The DPS-2 unit(s) shall be installed adjacent to the video intercom amplifier.

Contractor shall observe all local and national electrical and building codes.

**DPS-2 (TUV2)
Multi-Entrance
Video Switching Adaptor**

The Alpha Communications®/S.T.R.™ DPS-2 multi-entrance adaptors are used with our S.T.R.™ series video-intercom systems only. They provide video (camera) switching for two (2) to eight (8) entrances or remote cameras. In Europe, the DPS-2 is also known as the TUV2 (the European model#).

The DPS-2 adaptors are used in addition to the system amplifier, and power off of the same transformer. No additional transformer needed. The DPS-2 video switchers must be used with the TU1007A audio/door opener switchers. You need (1) DPS-2 for each TU1007A adaptor being used.

You must use one (1) DPS-2 switching adaptor for (2) camera locations, use two (2) for (3-4) camera locations, use three (3) for (5-6) camera locations and use four (4) for (7-8) building entrances, etc.

The DPS-2 multi-entrance adaptors are designed to easily surface mount right onto the finished wall by means of customer supplied screws or the convenient plastic 'Din Rail' bracket supplied with each switching adaptor. Connections are positive screw terminal type.

FEATURES

- Can be used for two (2) to eight (8) camera locations (or more)
- Operates on Safe Low-Voltage Class II Wiring
- Convenient Plastic 'Din Rail' Mounting Bracket
- Positive Screw Terminal Connectors

SPECIFICATIONS

Dimensions: Width: 2.50" (64mm)
Height: 4.00" (102mm)
Depth: 2.125" (54mm)
from mounting surface

Construction: Rugged ABS plastic casing.

Connections: Positive Screw Terminal Connectors.
Positive video cable clamps for coaxial cable connections

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.