

**#92011**

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Desk Master Control Station shall be Alpha Communications®/Stento model #92011 or approved equivalent. The master station shall be of aluminum desk housing finished in black epoxy with brushed aluminum trim. It shall be 3.50" H x 20.00" W x 8.00" D and contain 12 electronic selector buttons, with red and green LED indicators. The face plate shall include 4 function buttons and up/down volume controls. The master can operate by itself or in parallel with other masters or as a distributed remote master in a 9600 series intercom system. The master requires a model #92583 (12) pair cable and connector and a model #1117 24VDC 1.2 Amp power supply. The #92011 shall operate with all standard 9600 substations, on either Stento 9200 or 9600 intercom systems.

Contractor shall observe all local and national electrical and building codes.

#92011 12-Unit Desk Master Station

The #92011 is a high quality desk mount intercom master station, capable of handling calls from and direct-select access up to 12 remote substations. It is designed to operate either by itself, in a parallel with other masters or as a distributed remote master in a 9600 series intercom system. The #92011 is ideal for door control communication in jails and prisons, and as a building submaster in campus and similar building security systems. The #92011 will operate with all standard 9600 substations, on either Stento 9200 or 9600 series intercom systems.

FEATURES

- Compact 12 button master
- Crisp, clear voice communication
- Rugged, all Metal Desk Mount Housing
- Call annunciation by flashing LED and tone
- Programmable all call
- Lamp test and line fault test
- Stand-alone or multiple master use
- Parallel master or interface with 9600 series systems
- Simple installation

SPECIFICATIONS

Housing:	Aluminum desk housing finished in black epoxy with brushed aluminum trim.
Dimensions:	3.50" H x 20.00" W x 8.00" D (508mm) x (89mm) x (204mm)
Buttons:	12 electronic selector buttons, with red and green LED indicators. Face plate includes 4 function buttons and up / down volume controls
Amplifiers:	One 24 watt output to remote substations, One 12 watt output to master
Speaker:	3.00" (76mm) round, 45 ohm, 200-5000 Hz
Microphone:	Electret condenser, -65dB @ 1 Kz sensitivity
Remote Control:	Provision for optional remote control board
Handset:	Provision for optional (92497) handset kit
Wiring:	Requires #92583 (12) pair cable and connector
Power:	Requires #1117 24VDC 1.2 Amp power supply

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.