



#92012

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Rack Mount Master Control Station(s) shall be Alpha Communications®/Zenitel model #92012 or approved equivalent. The master station's housing shall be 1/8" thick aluminum with rack mount faceplate finished in Black epoxy. The master shall be 5.25" H x 19.00" W x 6.00" D and contain 12 electronic selector buttons, with red and green LED indicators. The face plate shall include 4 function buttons and up/down volume controls. The #92012 is capable of handling calls from and direct select access from up to 12 remote substations. The master can operate by itself or in parallel with other masters or as a distributed remote master in a 9600 series intercom system. The master requires a model #92583 pair cable and connector and a model #1117 24VDC 1.2 Amp power supply. The #92012 shall operate with all standard 9600 substations, on either Zenitel 9200 or 9600 intercom systems.

Contractor shall observe all local and national electrical and building codes.

#92012 12 Unit Rack Mount Master Station

The #92012 Master Control Station is a high quality rack mount intercom master capable of handling calls from and direct-select access up to 12 remote substations. It is designed to operate either by itself, in a parallel with other masters or as a distributed remote master in a 9600 series intercom system. The #92012 is ideal for door control communication in jails and prisons, and as a building submaster in campus and similar building security systems. The #92012 will operate with all standard 9600 remote substations, on either Stento 9200 or 9600 intercom systems.

FEATURES

- Compact 12 button master
- Crisp, clear voice communication
- Rugged, all metal Rack Mount Housing
- Call annunciation by flashing LED and tone
- Programmable all call
- Lamp test and line fault test
- Stand-alone or multiple master use
- Parallel master or interface with 9600 series system(s)
- Simple installation

SPECIFICATIONS

<u>Housing:</u>	1/8" Aluminum rackmount faceplate finished in Black epoxy
<u>Dimensions:</u>	5.25" H x 19.00" W x 6.00" D (134mm) x (483mm) x (153mm)
<u>Buttons:</u>	12 electronic selector buttons, with red and green LED indicators. Face plate includes 4 function buttons and up / down volume controls
<u>Amplifiers:</u>	One 24 watt output to remote substations, One 12 watt output to master
<u>Speaker:</u>	3" round, 45 ohm, 200-5000 Hz
<u>Microphone:</u>	Electret condenser, -65dB @ 1 Kz sensitivity
<u>Remote Control:</u>	Provision for optional remote control board
<u>Handset:</u>	Provision for optional (92497) handset kit
<u>Wiring:</u>	Requires #92583 (12) pair cable and connector
<u>Power:</u>	Requires #1117 24VDC 1.2 Amp power supply

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.