



#96257

#96257 Emergency Call Remote Station

The #96257 is a rugged, weather and tamper resistant intercom remote substation with a large red call-in button that is easily pressed by an elbow or shoulder. Call-in can be an emergency call to a 9200 or 9600 series Control Room Master. The remote station is extremely rugged and provides excellent sensitivity and voice reproduction. The #96257 is ideal for security in parking garages, stairwells, entry doors, gates, and police stations. The #96257 will operate on all 9200 and/or 9600 series intercom systems.

FEATURES

- Instant contact. . .in seconds
- Large Red "Mushroom" Button
- Rugged .25" machined metal
- No-penetration speaker grill
- Clear, crisp sound quality
- Weather resistant components
- Allows line supervision

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Emergency Call Remote Station shall be Alpha Communications®/Zenitel model #96257 or approved equivalent. The weather and tamper resistant station is 5.5" H x 7.5" W x 2.5" D with a 3" square speaker. The station shall have a large Red 1.5" round "mushroom" push button.

The station shall require 1 twisted pair #22 AWG to MDF (plus 2 pair for optional LED). The station shall be flush mount on #6297 box, surface mount on #6298 (interior) box or #6299 (exterior) box. The station is ideal for security applications. The #96257 emergency call station will operate on all Stento 9200 and/or 9600 series intercom systems.

Contractor shall observe all local and national electrical and building codes.

SPECIFICATIONS

| | |
|---------------------|---|
| Faceplate: | 0.25" machined, anodized, brushed aluminum, moisture gasket |
| Dimensions: | 5.50" H x 7.50" W x 2.50" D (139.7mm x 190.5mm x 63.5mm) |
| Speaker: | 3" Square, 45 ohm, 1 watt water resistant |
| Push Button: | Large, Red, 1.5" round, machined aluminum |
| Connectors: | Four (4) 10" pigtails |
| Protection: | Metal off-set speaker grill. Electronics and switch are encapsulated |
| Options: | LED call placed, or call connect, indicator is a system option |
| Cabling: | Requires 1 twisted pair #22AWG to MDF (plus 2 pair for optional LED) (Loop resistance not to exceed 100 ohms) |
| Mounting: | Flush mounts on #6297 box, surface mount on #6298 (interior) box or #6299 (exterior) box. (Mounting screws not provided) |

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.