

**LOH-2005**

### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

This Camera housing shall be Alpha Communications® model LOH-2005 or approved equivalent. Housing shall feature scratch resistant glass and be cadmium plated to resist rust. Housing can withstand a temperature range of -30° F to 150° F, and is designed for indoor or outdoor use. Housing shall be mounted from top or bottom and feature a removable top and bottom for easy access to camera and lens.

Contractor shall observe all local and national electrical and building codes.

**Check with applicable authorities regarding local and federal laws as they apply to party consent and video and/or audio recording.**

### LOH-2005 Indoor / Outdoor CCTV Camera Housing

#### FEATURES

- Lens window is scratch resistant glass
- Hardware is cadmium plated to resist rust
- Designed to allow for top or bottom mounting
- Tested to withstand temperatures from -30° F to 150° F
- Durable weatherproof housing cover is molded of rugged weather resistant ABS cyclocac material
- Removable top and bottom permits access to camera and lens while camera is kept mounted in place
- Housing base is made of lightweight corrosion resistant aluminum

#### MECHANICAL SPECIFICATIONS

**Dimensions:** 3.00" H x 5.75" W x  
15.375" L  
(70mm x 145 mm x 390mm)

**Weight:** 1 lb. 4 oz. (0.65 kg)

**Inside  
Maximum Height:** 2.25" (53mm)

**Inside  
Maximum Width:** 4.25" (110mm)

**Max. Camera  
Lens Length:** 13.0" (337mm)

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*