



Product Specification Sheet



APS235

Rev. 3 - 03/2011



L-101 / L-102

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The corridor dome light(s) shall be Alpha Communications® L-101, and the corridor zone lights shall be Alpha Communications®/Tektone L-102, or approved equal. Light(s) shall include a translucent plastic cover mounted on a stainless steel mounting plate, which shall be removable for bulb replacement, without the use of any tools. The L-101 and L-102 shall be U.L. 1069 listed, to the latest standards. Unit(s) shall mount over a conventional 1-gang electrical 'gem' back box.

Contractor shall observe all local and national electrical and building codes.

L-101 Corridor Light L-102 Corridor Zone Light

The Alpha Communications® L-101 corridor dome light (with single white bulb) and L-102 corridor zone lights (with white and red bulbs) provide visual indication of any type of call when used with a nurse-call, emergency-call, or for stand-alone signaling applications.

When used with the NC110A, NC110N, NC150N, NC150R or NC200N series nurse-call systems, emergency calls are indicated by the rapid flashing of the L-101 corridor dome light associated with the calling station. Normal (routine) calls produce a steady illumination. The L-102 corridor zone light indicates an emergency call by the rapid flashing of the red lamp associated the zone or area from which an emergency call has been placed. Normal calls are indicated by a steady illumination of the white lamp. They can also be used with our AlphaEcall and CM800 series emergency-call system(s).

Both models mount on a standard 1-gang electrical back box and feature an easily removable white translucent cover for quick bulb replacement, without the use of any tools required.

Optionally, the L-101 is also available with a single RED bulb (model L-101R) or a single BLUE bulb (model L-101B), instead of the single WHITE bulb.

FEATURES

- U.L. 1069 Listed - 4th Edition Standards
- Operates on 24VAC or 24VDC
- Easy Bulb Replacement - No Tools Required
- Stainless Steel Plate with White Translucent Cover
- Excellent Visibility

SPECIFICATIONS

Dimensions:	Height: 4.50" (115mm)
	Width: 1.75" (70mm)
	Projects: 2.50" (64mm) from mounting surface
Mounting:	Mounts over standard 1-gang electrical back box with plaster ring (model IH357 with model IH358).
Finish:	Translucent white plastic cover mounted on a stainless steel mounting plate.

WIRING REQUIREMENTS:

See the specific system wiring diagram for more complete wiring information.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.

Copyright© 1998-2011, Alpha Communications®, All Rights Reserved