



## AB707 3-Call Desk/Wall Remote Station with Display

The AB707 remote station is similar to the AA701 master station, but has a limited keypad. It has 3 dial buttons which are programmed to call station numbers 11, 12 and 13 only. When these buttons are used in combination with the X-button (X + call button), calls can be made to subscriber no. 21 (X + 11), Program Distribution Channel (X + 12) or subscriber no. 23 (X + 13). The station is also equipped with T, O, and X buttons, volume up, volume down and confidential mode (handset function).

### FEATURES

- Clear two-way communications
- Rugged High-Impact ABS plastic finish
- Can be Desk or Surface Wall Mounted (with bracket)
- Built-in LCD Display
- No Central Exchange Required
- Simple to install
- Simple loop wiring

### SPECIFICATIONS

<b>Color:</b>	Beige
<b>Dimensions:</b>	Depth: 2.5" (64mm) Width: 3.0" (78mm) Height: 8.4" (214mm)
<b>Weight:</b>	.55 lb. (250g)
<b>Finish:</b>	High-grade, impact-resistant ABS plastic with a satin finish
<b>Connector:</b>	Plug-in cable (required)
<b>Mounting:</b>	Desk (standard) or surface wall mount with optional <b>GF632A</b> wall mounting bracket.

### REQUIRED COMPONENTS

**Select one of the following connector cables:**

<b>BF640</b>	6 foot (8-pin) straight connector cord/plug
<b>BF641</b>	20 foot (8-pin) straight connector cord/plug
<b>BF642</b>	7 foot (8-pin) coiled connector cord/plug
<b>BF643</b>	1 foot (8-pin) coiled connector cord/plug

**KB170** Wall mounting connector plate, mounts on 1-gang electrical 'gem' box.

**PSDC24xxx** Series 24VDC system power supply (1 required per system) xxx=capacity

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*

### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The PRO700 remote station(s) shall be Alpha Communications® model AB707 or approved equivalent. Remote(s) shall be made of high-grade, impact-resistant Beige ABS plastic with a satin finish, and shall plug into a model KB170 wall connector plate. Remote(s) shall require a plug-in cable (models BF640, BF641, BF642, or BF643). Remote(s) shall feature 3 direct dialing buttons, built-in LCD display and shall require simple loop wiring, with no central station required. Remote(s) shall be desk mount type and can be surface wall mounted using an optional model GF632A wall mounting bracket. System shall power off of a single PSDC24 series 24VDC system power supply. The PRO700 series system shall be expandable to a maximum of 40 total master and/or remote stations.

Contractor shall observe all local and national electrical and building codes.