



**AB709**

## AB709 3-Call Surface Mount Remote

The AB709 station is similar to the surface Master Station model AA702, but without display. It is designed for indoor conditions and is suitable as a door station.

The keypad has 3 direct dial buttons which are programmed to call station number 11, 12, and 13. When these buttons are used in combination with the X-button (X+ call button), calls can be made to subscribe no. 21 (X+11), Program Distribution Channel (X+12) or subscriber no. 23 (X+13). The station is also equipped with a cancel button (X).

The surface mounted station can easily be converted to a flush mounted model by using the clip-on front plate BF636 and the BBF602 flush backbox.

### FEATURES

- Clear two-way communications
- Rugged High-Impact ABS plastic finish
- Can be door station
- For indoor use
- No Central Exchange Required
- Simple to install
- Simple loop wiring

### SPECIFICATIONS

<b><u>Color:</u></b>	Beige
<b><u>Dimensions:</u></b>	Depth: 2.0" (51mm) Width: 3.1" (80mm) Height: 8.7" (220mm)
<b><u>Weight:</u></b>	.77 lb. (350g)
<b><u>Finish:</u></b>	High-grade, impact-resistant ABS plastic.
<b><u>Connector:</u></b>	Positive screw terminals
<b><u>Mounting:</u></b>	Surface (standard). Can be flush mounted using the BF636 plate and BBF602 flush backbox.

### REQUIRED COMPONENTS

<b><u>PSDC24xxx</u></b>	Series 24VDC system power supply (1 required per system) xxx=capacity
-------------------------	--

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*

### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The PRO700 remote station(s) shall be Alpha Communications®/Ring model AB709 or approved equivalent. Remote(s) shall be made of high-grade, impact-resistant Beige ABS plastic with a satin finish. Remote(s) shall be equipped with 3 direct dial button which is programmed to call station numbers 11, 12, and 13. Remote(s) shall require simple loop wiring, with no central station required. Remote(s) shall be surface wall mount type and can be flush wall mounted using an optional model BF636 wall mounting plate with model BBF602 flush steel backbox. System shall power off of a single PSDC24 series 24VDC system power supply. The PRO700 series system shall be expandable to a maximum of 40 total master and/or remote stations.

Contractor shall observe all local and national electrical and building codes.