



SF102

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The visual double patient station(s) shall be Alpha Communications®/Tektone SF102, or approved equal and shall include a single lighted 'CALL-PLACED' indicator, a 'CANCEL' button, and two (2) jacks for the required model SF301/8 (single) call-cords (or other specialty type cords as required). A call will be registered at the annunciator panel(s), corridor light(s) and any optional corridor zone lights. The station's 'CALL-PLACED' LED will light if the call switch is pushed or of the call-cord is removed from its jack. All electronic components needed for these features and functions shall be mounted on a printed circuit board and all station components shall be mounted on a rugged ABS (White) plastic faceplate. The station shall be mounted into a standard single gang electrical box (or ring). A plug-in connector shall be provided for connections. Contractor shall observe all local and national electrical and building codes.

Copyright© 1999-2011, Alpha Communications®, All Rights Reserved

SF102 Double Bed Visual Patient Station

The Alpha Communications® SF102 visual patient station includes two (2) jacks for the insertion of two (2) required model SF301/8 (single) call cord sets (or equivalent). The SF102 is used primarily with the NC110A or NC110N series visual nurse-call system. A call is registered at the annunciator panel and corridor light (and corridor zone light if installed) when the call cord button is used, or if the call cord is accidentally removed from the jack. The station includes a single lighted 'CALL-PLACED' indicator when a call is placed and a 'CANCEL' button, mounted on a rugged ABS white plastic faceplate.

FEATURES

- Simple Push-button Calling (using required call cords)
- Lighted CALL-PLACED Indicator (single)
- Call-reset CANCEL Push-button
- Call Automatically Registers if either Call Cord is Accidentally Removed
- Flame Retardant type ABS White Plastic Faceplate
- Corridor Zone Light Capability (optional)

SPECIFICATIONS

Dimensions:	Height: 4.50" (114mm)
	Width: 2.75" (69mm)
	Depth: 1.75" (44mm)
	Projects: 0.44" (11mm) from mounting surface
Mounting:	Steel City #52171 box with Steel City #52C14 plaster ring, or Alpha Communications® Model #IH358 box with IH357 ring, or EXACT EQUAL. Vertical mount.
Construction:	Flame retardant type ABS plastic faceplate. Switches and electronic components are circuit board mounted.
Connections:	Plug-in connectors.

REQUIRED COMPONENTS

NC110N	Annunciator Panel
PK152	Control Unit with SS106 Transformer
SF301/8	Call-cords (or equivalent models)

OPTIONAL COMPONENTS

LI381	Corridor Dome Light w/1 Bulb
LI382	Corridor Dome/Zone Light w/2 Bulbs
SF155B	Emergency Pull/Push Station (Toilet)
SF337C	Emergency Pull/Push Station (Shower)

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.