



# Product Specification Sheet



APS340

Rev. 9 - 06/2011



**OH600  
Flush  
Backbox  
(shown in a  
vertical  
configuration -  
is sometimes  
used in a  
horizontal  
configuration)**



**OH601  
Flush  
Backbox**

## OH600 / OH601 Flush Backboxes

The Alpha Communications® models OH600 and OH601 are flush mounting backboxes. The OH600 is made of galvanized steel and the OH601 is made of steel, painted in a Grey powder coat epoxy painted finish for durability, or in galvanized steel

They are our most popular flush mounting boxes, and are used with a variety of flush mount intercom entry lobby panels, and remote intercom stations.

The painted boxes are finished on top, bottom, both sides, and the back and both models have standard electrical knockouts on the top and bottom (when mounted vertically), to allow for wire access.

These boxes are designed to be attached to mounting studs or set directly into a concrete or masonry wall.. An adjustable 'tinnerman' mounting clip on the top and bottom (when mounted vertically) allows the finished panel/station to be mounted level, even if the back box is installed slightly crooked.

They are typically used with the ES612, AM612 and AM642 series lobby entry panel stations, but can be used with other stations as well. The OH600 can also be used with the IR150SS area of rescue assistance remote station(s), when mounted horizontally.

### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The flush back box(es) shall be Alpha Communications® model OH600 or OH601 or approved equal. The OH600 shall be made of galvanized steel and the OH601 shall be made of steel, and painted in a Grey powder coated epoxy finish, or of galvanized steel. All models shall have standard electrical knockouts on the top and bottom (when mounted vertically), to allow for wire access.

Contractor shall observe all local and national electrical and building codes.

### DIMENSIONS

**OH600:** Height: 10.25" (261mm)  
Width: 4.25" (108mm)  
Depth: 2.00" (51mm)  
(when mounted vertically)

**OH601:** Height: 16.25" (413mm)  
Width: 4.25" (108mm)  
Depth: 2.00" (51mm)

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*