



**KKA (Aluminum)
Model Shown**

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The key keeper(s) shall be Alpha Communications®/ Florence KK series, or approved equal. Key Keeper faceplate shall be constructed of striated aluminum finish. The key keeper(s) shall be ('loose key') model KKA-Natural Aluminum, KKG-Gold Color or KKD-Dark Brown. The Key Keeper(s) shall be flush mounted into the finished wall surface. The Key Keeper door hinge shall be fully hinged to minimize vandalism and unauthorized opening. Contractor shall install the key Keeper as per all U.S. Postal Service regulations. Key Keeper(s) shall include postal lock mounting bracket and screws required. Key Keeper shall be mounted (horizontally or vertically).

Contractor shall install as per USPS regulations.

Copyright© 1995-2005, Alpha Communications®, All Rights Reserved

KK Series Aluminum Flush Mount Key Keepers

The Alpha Communications® KK series flush mount key keepers are designed specifically to mount in conjunction with aluminum lobby panels, directories or mail boxes.

The KK series key keepers are U.S. Postal Service Approved, and are required when mailboxes are installed behind a locked entry door. This allows the Postman access to the mail boxes, without having to bother (or wait for) any of the building's tenants.

These key keepers can be mounted vertically or horizontally and include the mounting hardware for the installation of the postal lock (supplied by the local post office).

The KK series key keepers are designed to be flush mounted only. U.S. Postal Service regulations do not allow for a key keeper to be surface mounted. The KK series key keepers are available in three (3) colors (all 'loose key' type) Natural Anodized Aluminum (**model KKA**), Gold Painted over Aluminum (**model KKG**), and Dark Brown over Aluminum (**model KKD**)

FEATURES

- Striated Aluminum Front Faceplate - Resists Scratches
- Easy Installation
- Can be Mounted Vertically or Horizontally
- Mounts flush into the Finished Wall
- Available in three (3) colors and other custom colors
- U.S. Postal Service Approved

SPECIFICATIONS

Dimensions: Wall Opening: 4.38"W (112mm) x 4.75"H (121mm) x 2.63"D (67mm) installed vertically. Outside Dimensions: 6.25"W (159mm) x 6.78"H (173mm) installed vertically.

Construction: Heavy Duty Stainless Steel Faceplate.

Hinge Type: Full length hinge assembly on short side.

Mounting: Flush. Predrilled mounting holes.

Models: **KKA** Natural Anodized Aluminum
KKD Dark Brown over Aluminum
KKG Gold Painted over Aluminum

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.