



Product Specification Sheet



APS388

Rev. 1 - 09/1998



#9621

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Tamper Resistant Indoor Remote Station(s) shall be Alpha Communications®/Stento model #9621 or approved equivalent. The tamper resistant station is 4.5" H x 4.5" W x 2.5" D with a 2" square speaker. The station shall have a large 1.0" round, nickel plated, call-in push button.

The station shall require 1 twisted pair #22 AWG to the master station. The station shall be flush mount on a customer supplied standard 2-gang, deep masonry box. The station is ideal for high security indoor applications. The #9621 emergency call station will operate on all Stento 9200 and/or 9600 series intercom systems.

Contractor shall observe all local and national electrical codes.

#9621 Tamper Resistant Indoor Remote Station

The #9621 is a compact, tamper resistant intercom remote substation with a unique design to protect the speaker, call button and internal electronics from external abuse. Call-in can be an emergency call to a 9200 or 9600 series master station. The remote station is extremely rugged and provides excellent sensitivity and voice reproduction. The #9621 is ideal for jail cells, prison day rooms, parking garages, stairwells, entry doors, and police stations. The #9621 will operate on all 9200 and/or 9600 series intercom systems, and is designed for indoor use only.

FEATURES

- Clear Two-Way Communications
- Heavy Duty Call-In Button
- Rugged Stainless Steel Faceplate
- No-penetration Speaker Grille
- Clear, crisp sound quality
- Simple to Install
- Allows line supervision

SPECIFICATIONS

Faceplate:	11 gauge, #304 Stainless Steel
Dimensions:	4.50" H x 4.50" W x 2.50" D (115mm x 115mm x 63.5mm)
Speaker:	2" Square, 45 ohm, 1 watt
Push Button:	1.0" round, heavy duty machined brass, nickel plated snap action with wiping gold plated contacts
Connectors:	Positive Screw Terminals
Cabling:	Requires 1 twisted pair #22AWG to Master (Loop resistance not to exceed 100 ohms)
Mounting:	Standard 2-gang deep masonry box (supplied by others). (Mounting screws not provided).

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.