



#62927

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Security Intercom Outdoor Remote Station(s) shall be Alpha Communications®/Stento model #62927 or approved equivalent. The weather and tamper resistant station is 5.50" H x 7.50" W x 2.50" D with a 3" square speaker. The station shall have a large Red 1.50" round "mushroom" push button.

The station shall require 2 twisted pair #24AWG to exchange loop. The station shall be flush mount on #62927 box, surface mount on #6298 (interior) box or #62991 (exterior) box. The station is ideal for security applications. The #62927 security intercom station will operate on all Stento AlphaCom, CRT or CRM series intercom systems.

Contractor shall observe all local and national electrical codes.

#62927 Security Intercom Outdoor Remote Station

The #62927 is a rugged, weather and tamper resistant intercom remote substation with a large red call-in button that is easily pressed by an elbow or shoulder. Call-in can be programmed as an emergency call to a Control Room Master (CRM), AlphaCom or Call Handler System (CRT). The remote station has a unique design to protect the speaker, microphone, LED and internal electronics from moisture and external abuse. The remote station, which is extremely rugged and provides excellent sensitivity and voice reproduction, is ideal for security applications in parking garages, stairwells, campus walkways, entry doors, gates, and police stations.

FEATURES

- Instant contact. . .in seconds
- Large Red "Mushroom" Button
- Rugged .25" machined metal
- No-penetration speaker grill
- Clear, crisp sound quality
- Weather resistant components

SPECIFICATIONS

Faceplate:	0.25" machined, anodized, brushed aluminum, moisture gasket
Dimensions:	5.50" H x 7.50" W x 2.50" D (139.7mm x 190.5mm x 63.5mm)
Speaker:	3" Square, 45 ohm, 1 watt water resistant
Push Button:	Large, Red, 1.50" round, machined aluminum
Indicator:	LED behind translucent red epoxy bonded lexan lens
Connectors:	Four (4) 10" pigtailed
Options:	LED call placed, or call connect, indicator is a system option
Cabling:	Requires 2 twisted pair #24AWG to exchange loop. (Loop resistance not to exceed 240 ohms)
Mounting:	Flush mounts on #6297 box, surface mount on #6298 (interior) box or #62991 (exterior) box. (Mounting screws not provided)

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.