



Product Specification Sheet



APS489

Rev. 1 - 01/2002



MV-12

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

This video monitor(s) shall be Alpha Communications® model MV-12 or approved equivalent. Monitor(s) shall have large 12" picture (measured diagonally). Monitor(s) shall have front mounted controls and built-in 2-channel manual switcher. Monitor(s) shall have a high resolution of more than 800 lines and operate on 100VAC to 240VAC. Monitor(s) shall operate under a temperature range of 14° F to 122 ° F (-10° C to 50° C).

Contractor shall observe all local and national electrical and building codes.

Check with applicable authorities regarding local and federal laws as they apply to party consent and video and/or audio recording.

MV-12 12" High Resolution B & W Video Monitor

FEATURES

- All front mounted controls
- Large 12" picture (measured diagonally)
- Bright high contrast display / high gain video amplifier
- Built-in 2-channel manual switcher
- High resolution - more than 800 lines
- Universal Power Supply (100 to 240 VAC, 50/60 Hz.)
- Optimum stability with time lapse recorders
- Optional Rack Mounting available

CRT

Size: 12.0" (measured diagonally)

ELECTRICAL SPECIFICATIONS

Bandwidth: 10 Mhz (-3 dB)

Scanning Frequency: 15.75 KHz (EIA), 15.625 KHz (CCIR)

Vertical Scan Frequency: 50 / 60 Hz (auto switch)

Video Connectors: BNC in/out x 2 sets

Input Voltage: 100 to 240 VAC

Power Consumption: 20 watts maximum

MECHANICAL SPECIFICATIONS

Dimensions: 12.50" H x 12.00" W x 12.13" D (318mm x 305mm x 309mm)

Weight: 9.75 lbs. (4.4 kg)

ENVIRONMENTAL

Temperature: 14°F to 122°F (-10°C to 50°C)

Humidity: 0 to 90 %

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.