



**VDP-3000 (2-wire)
Video-Intercom Kit**

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The video-intercom kit(s) shall be Alpha Communications® VDP-3000 or approved equal. Monitor shall be surface mounted using the provided mounting bracket. Monitor shall include a high quality 4.0" flat screen. Monitors using mirrors or other non-flat type screens shall not be acceptable. Monitor handset shall feature electret condenser microphone for exceptional voice fidelity. Handsets that include carbon transmitter or other voice technologies shall not be acceptable. Monitor shall include a door release button. Monitor shall plug directly into a standard 110VAC/60Hz. electrical wall outlet, and shall provide the power for the electronic chime, video monitor and camera, and intercom. Monitor shall be finished in White plastic. A separate low-voltage power supply shall be used to power the electric door release, if required.

The door remote station shall be surface mount type and shall include a 1/3" Black and White CCD camera, infrared illuminators and momentary call button. Unit shall be finished in Soft Grey plastic.

Contractor shall observe all local and national electrical codes.

Copyright© 2002, Alpha Communications®, All Rights Reserved

VDP-3000 Video-Intercom Kit

The Alpha Communications® VDP-3000 video-intercom kits are designed to meet your requirements for video-intercom security, for a single entry door to a single inside video monitor unit.

The attractive monitor conveniently surfaces mounts right on the wall, using a provided wall mounting bracket. Monitor simply plugs into a standard 110VAC/60Hz. electrical outlet, and provides power for the electronic chime, video monitor/camera and intercom.

The video monitor features a crystal clear 4.0" black and white flat screen monitor (measured diagonally), electronic chime signalling, coiled cord and a momentary door release switch. The monitor also features a front-mounted 'ON' button to turn the monitor on without being called from an entrance panel.

The door camera/intercom station is fully surface mounted and includes a built-in 1/3" CCD Black and White camera, infrared illuminators, and a momentary call button. Door camera remote is finished in Soft Grey plastic.

FEATURES

- 4.0" (diagonal) Crystal Clear Black & White video screen
- Convenient Duplex Voice Operation
- Easy Installation (only 2 wires from monitor to door unit)
- Clear Voice Fidelity using Electret Condenser Microphones
- Rugged and Reliable. Simple to Operate

WIRING REQUIREMENTS

From the inside monitor station to the outdoor remote camera station, run a 2-conductor #18AWG cable, up to 50 meters (approx. 165 feet). This cable will provide the wiring needed for the electronic chime signal, camera power, camera video signal and intercom signal. No coaxial cable is needed!

If an electric door opener will be used, run an additional 2-conductor #18AWG cable, up to 50 meters (approx. 165 feet) from the video monitor to the door opener, as well as from the video monitor to the door opener transformer/power supply.

System power is provided by plugging the inside monitor unit into a standard 110VAC/60Hz. electrical outlet.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.