



Product Specification Sheet



APS522

Rev. 2 - 07/2003



UPG1 (shown)



UPG6/2 (shown)

UPG Series Flush Housings for Modular Series Door Stations

The UPG flush plastic housings are designed to be used with the Alpha Communications®/S.T.R.™ modular series door entry stations. There are seven (7) configurations available in single and double-width varieties. The UPG housings are designed to be used in conjunction with the MT series Modular Frame(s). For larger configurations, multiple UPG housings and MT frames may be 'ganged' together.

The UPG housings have snap-in stand-offs to allow mounting of the individual modular snap-in component's PC boards, for easy and neat system wiring.

See chart below for reference of sizes/types and configurations available.

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

Flush plastic housing(s) shall be Alpha Communications®/S.T.R.™ UPG series or approved equal. Flush housing(s) shall be modular type and shall be used in conjunction with the proper MT series modular panel frame(s). The UPG plastic housing(s) shall contain built-in stand-offs to allow mounting of the individual modular snap-in component's PC boards, for easy and neat system wiring.

UPG housing(s) shall be made of durable plastic, and shall flush mount into the finished wall.

Contractor shall observe all local and national electrical and building codes

CONFIGURATIONS AVAILABLE

Model#	# of			
	Modules	Height	Width	Depth*
UPG1	1W x 1H	4.40"	4.40"	1.58"
UPG2	1W x 2H	8.35"	4.40"	1.58"
UPG3	1W x 3H	12.28"	4.40"	1.58"
UPG4	1W x 4H	16.22"	4.40"	1.58"
UPG4/2	2W x 2H	8.35"	8.35"	1.58"
UPG6/2	2W x 3H	12.28"	8.35"	1.58"
UPG8/2	2W x 4H	16.22"	8.35"	1.58"

*Depth indicates size from front to back of flush housing, although housing may be placed somewhat deeper into wall recess.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.