



Product Specification Sheet



APS529

Rev. 1 - 02/2003



BMMW Motion Detector Module (shown in White)

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

Motion detector module(s) shall be Alpha Communications®/S.T.R.™ BMM Series or approved equal. Motion detector module(s) shall snap into the corresponding MT series modular panel frame(s).

Motion detector module(s) shall be finished in Titanium (suffix-T), White (suffix-W) or Brown (suffix-B), and shall offer a 180 degree angle of view for 1 to 4 meters distance. Motion detector module(s) shall have time adjustment of 5 seconds to 8 minutes, and shall provide a relay contact closure of 2A.

Contractor shall observe all local and national electrical and building codes

BMM Series Motion Detector Module for Modular Series Door Stations

The BMM Series motion detector modules are designed to be used with Alpha Communications®/S.T.R.™ modular series door entry stations.

The BMM Series motion detector modules are used for detection of movement in the entry area by the modular door station(s).

All IM motion detector modules are available in three (3) finishes; Titanium (suffix-T), White (suffix-W) or Brown (suffix-B).

All IM motion detector modules are 3.94" w x 3.94" h (100mm x 100mm), and are made to snap into the MT series modular panel trim frame(s).

To service the BMM Series modules, once installed, use the model 13510 key / tool unit.

SPECIFICATIONS

<u>Lens Angle:</u>	Horizontal max. 180 degrees
<u>Dimensions:</u>	3.94" H x 3.94" W (100mm x 100mm)
<u>Time</u>	
<u>Adjustment:</u>	5 seconds to 8 minutes
<u>Control:</u>	Adjustable twilight control with compensation for natural light
<u>Output:</u>	Switch contact 24V max. 2A
<u>Area of Detection:</u>	1-4 meters standard (max. 12 meters depending upon height of installation)

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.