



IR150SS (Flush Mount)



IR150SS/S (Surface Mount)

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

Remote call station(s) shall be Alpha Communications®/ Tektone IR150SS (flush mount) and/or IR150SS/S (surface mount) or approved equal. Station(s) shall provide a call-placed indicator, a 2.36" (60mm) mushroom-style call push button, a cancel button and an audio-on indicator. The station(s) shall include a 3.50" round speaker/microphone with voice response. All components of the station shall be mounted on a durable brushed Stainless Steel faceplate. Positive screw terminals shall be used for electrical connections. The IR150SS shall flush mount over a model OH600 back box (mounted horizontally). The IR150SS/S shall surface mount right on the surface of the wall, without the need for a back box. When used with the NC150R series system, contractor shall furnish and install a model SN-C41 raised letter/Braille self-stick 'PUSH FOR HELP' sign, adjacent to each IR150SS and/or IR150SS/S remote call station.

Contractor shall observe all local and national (and electrical (and A.D.A.) codes.

PLEASE NOTE: As of March 2009 the IR150SS and IR150SS/S Remote Call Stations no longer have black or red coloring within the engraved button labels (as shown above). During a review of the current ADA specifications, it was determined that the coloring was not required.

IR150SS and IR150SS/S Area of Rescue Remote Call Stations

The Alpha Communications® IR150SS (flush) and IR150SS/S (surface) Remote Call Stations may be used to provide efficient communications to the NC150R (and/or NC150N) Area of Rescue Master Control Station(s).

IR150SS and/or IR150SS/S Remote Call Stations are located in areas of rescue assistance, to provide two-way hands-free communication to a central location from which help may be summoned. Calls are placed by pressing a large, 2.36" (60mm) mushroom-style momentary pushbutton. Solid state indicators on the faceplate indicate when a call has been placed and when the intercom is in use.

FEATURES

- Push button calling via large mushroom-style pushbutton
- Call-placed indicator
- Audio-on indicator
- Reset button
- Sensitive speaker/microphone
- Attractive and durable Stainless Steel faceplate

SPECIFICATIONS

Dimensions:	Height: 5.00" (127mm)
	Width: 11.2" (285mm)
IR150SS	Depth: 2.00" (51mm) (flush box)
	Projects: 1.50" (38mm) above mounting surface
IR150SS/S	Depth: 2.00" (51mm) (surface bends)
	Projects: 1.50" (38mm) above faceplate surface
Construction:	Durable Stainless Steel faceplate
Button:	2.36" (60mm) diameter mushroom-style
Speaker/Mic:	3.50" (89mm) with voice response
Connections:	Positive screw terminals (6)
Housings:	Flush mounting box (OH600)
	horizontal mount - steel - for IR150SS

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.