



SF301DIG

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

Digital Pillow Speaker(s) shall be Alpha Communications®/TekTone model SF301DIG or approved equal, and shall be suitable for use in general or oxygen environments. Pillow speakers shall have a 2.75" Mylar® cone speaker. The pillow speaker case shall be constructed of flame-retardant ABS plastic. All momentary contact SPST 10 AMP switches shall be rated for over 1 million operations. The pillow speaker cord shall be an 8 feet long and shall have an 8-pin 'DIN' plug at the end. The cord shall also be provided with stain relief. Each pillow speaker shall be provided with a wall hanger and security clip,

Controls shall be provided for volume, nurse call, lamp, and television and radio functions. The pillow speaker shall be capable of switching automatically from entertainment audio to intercom audio when used with the appropriate modules. The pillow speaker shall be Electro-Static-Discharge (ESD) protected to over 12,000 volts.

The SF301DIG shall be UL® 1069 listed.

SF301DIG 'Digital' Pillow Speakers

The Alpha Communications® SF301DIG 'Digital' Pillow Speakers are used primarily with the IR311B/C and IR312B/C patient stations for the NC300II series microprocessor nurse-call system(s).

The SF301DIG provides for call placement to the system master station(s) as well as remote TV analog/digital control. When used in conjunction with the PM311C or PM312C Pillow Speaker Intercom Modules, the unit also supplies two-way, hands-free communications with the master station, and automatic silencing of TV and Radio audio, while the intercom is in use. When used with the RY350B Radio Relay, the SF301DIG provides 4-channel radio control.

To call a nurse simply press the pushbutton identified by the white cross. Separate pushbuttons are provided for TV ON/OFF, channel selection UP/DOWN, Closed Captioning and Radio ON/OFF. Buttons are also provided for Volume UP/DOWN, and room and reading light controls.

FEATURES

- UL 1069 Listed
- Oxygen Safe
- Mylar® cone speaker
- Flame-retardant ABS plastic
- SPST switches - rated for over 1 million operations
- ESD protected over 12,000 volts
- Hanger and security clip provided
- 8 foot cord with 'DIN' plug
- Provides pillow speaker intercom (when used with the appropriate modules)
- Provides 1-2 lamp controls (when used with the appropriate modules)
- Provides 4-channel radio controls (when used with the appropriate modules)

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.