



Product Specification Sheet



APS597

Rev. 1 - 06/2005



**6304C B&W DigiBus™
COLOR Monitor
(Giotto Style)**

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The DigiBus™ LCD COLOR apartment monitor station(s) shall be Alpha Communications®/Elvox™ (Giotto Series) model 6304C, or approved equal. Monitor(s) shall be surface mounted on the surface of the finished wall (or over an adaptor plate to cover the existing oversized flush backbox). Monitor(s) shall include a high quality 4.0" (102mm) LCD COLOR video screen (measured diagonally). Monitor handset shall feature duplex communication and electret microphone for exceptional voice fidelity. Handset shall include a heavy duty coiled cord. Monitor(s) shall include a door release button, monitor ON button, contrast/brightness control switch, two (2) auxiliary switches and steel backplate connector. Each model 6304C monitor shall have one (1) auxiliary alarm input, which upon momentary "dry" contact activation, shall send an alarm signal to the model 945B (or PC or other) master (concierge) station(s). Monitor(s) shall be constructed of high impact ABS plastic in a soft white color. Monitor(s) shall feature electronic call tone signaling from lobby entrance station(s).

Contractor shall observe all local and national building and electrical codes.

Copyright© 2005, Alpha Communications®, All Rights Reserved

6304C B&W DigiBus™ Apt. COLOR Video Monitor

The Alpha Communications®/Elvox™ 6304C (Giotto) apartment house DigiBus™ series digital-dial LCD COLOR monitors are designed to meet virtually any requirement for low-rise and high-rise apartment video-intercom security, where digital-dial type entry panels are required.

These attractive monitors surface mount right onto the wall, by means of a steel backplate (supplied) or over an optional flush steel backbox with plaster ring (IH358 with IH357).

All 6304C monitors feature a crystal clear 4.0" (102mm) LCD COLOR monitor (measured diagonally), electronic tone signalling, heavy duty coiled cord, momentary door release button, monitor activation button, contrast control and amplified handset with electret microphone, providing simultaneous Talk and Listen functions. Each model 6304C monitor shall have one (1) auxiliary alarm input, which upon momentary "dry" contact activation, shall send an alarm signal to the model 945B (or PC or other) master (concierge) station(s).

When combined with the digital-dial entry stations and model 6948 amplifier/power supply (and related accessories), the 6304C monitors are part of a complete building security system.

FEATURES

- 4.0" (diagonal) LCD COLOR Video Screen
- Convenient Duplex Voice Operation
- Easy Surface Wall Installation using Steel Wall Plate
- Quick Wall Plate Connect/Disconnect
- Clear Voice Fidelity using Amplified Handset
- Rugged and Reliable. Simple to Operate
- Pleasant Electronic Call Tone Signal from Entrance Panel(s)
- Low profile flush monitor protrudes only 3.50" from wall
- Works with a Variety of Digital-Dial Lobby Entry Panels with color camera(s), and/or Concierge Stations

SPECIFICATIONS

- Dimensions:** All 6304C monitors are 8.00"W (204mm) x 8.75"H (223mm) x 2.80"D (72mm). All dimensions shown are outside dimensions, less the coiled cord.
- Handset:** Duplex Handset with Electret Microphone and heavy duty coiled cord.
- Finish:** High Impact ABS Plastic, Soft White color
- Controls:** Door Release Button, Monitor Button, Contrast/Brightness Control, 2 auxiliary switches.
- Video Tube:** 4.0" (102mm) High Brightness LCD COLOR screen (measured diagonally).
- Options:** Model IH358 flush double gang electrical box, used with model IH357 flush mount plaster ring.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.

Elvox and DigiBus are registered trademarks of Paso Sound Inc.