



# Product Specification Sheet



APS601  
Rev. 2 - 11/2005



**PSR-4/24 (4 Amps)**  
**(shown less power cord)**

## ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The 24VDC system Power Supply shall be Alpha Communications®/Speco PSR-4/24 or approved equivalent. Unit shall be used with the AlphaStatus™ room status or other similar system application(s). Unit shall provide 24VDC power and shall operate on 60 Hz. Power supply shall be provided with an AC cord and grounded plug. Regulated power supply shall be U.L. listed. Contractor shall provide a power supply of sufficient amperage, depending upon the total number of master and/or remote devices in the system.

Contractor shall observe all local and national electrical and building codes.

## PSR-4/24 AlphaStatus™ 24VDC Power Supply Unit

The PSR-4/24 24VDC regulated power supplies are specifically designed to provide power for the AlphaStatus™ series room status system(s) or other similar application. Typically, one (1) power supply is required for each system, but depending on the number of room devices, more may be required.

### FEATURES

- 24VDC, 60 Hz Output
- Heavy duty construction
- 4 Amps constant output, 5 Amps surge
- U.L. Listed (for U.S. use)

### SPECIFICATIONS

<b>Housing:</b>	Heavy duty steel case finish, with mounting feet
<b>Output:</b>	24VDC, 60 Hz, Regulated <b>4 Amps Constant (5 Amps surge)</b>
<b>Overload Protection</b>	Fuse and auto reset circuit breaker
<b>Input:</b>	117VAC, 60 Hz, single phase
<b>Connectors:</b>	AC cord with grounded plug and universal binding posts
<b>Switch:</b>	On/Off toggle type
<b>Size:</b>	6.50"W x 4.00"H x 6.50"D (166mm) x (102mm) x (166mm)
<b>Weight:</b>	4 lbs.

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*