



NG333 Power Supply

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Power Supply unit(s) shall be Alpha Communications®/S.T.R.™ QwikBUS™ model NG333, or approved equal. The NG333 shall be built into a rugged high impact Grey ABS plastic case, and shall be powered a contractor supplied power cord. Contractor shall furnish the proper C333-4 connecting cable to connect to the SP333 intelligent controller.

Low voltage wiring shall be used and positive screw terminal and plug-in connectors shall be provided for installation wiring. The NG333 shall be mountable right to the surface of the wall or in a customer-supplied junction box cabinet.

Contractor shall observe all local and national electrical and building codes.

Copyright© 2007, Alpha Communications®, All Rights Reserved



NG333 Switching Power Supply

The Alpha Communications®/S.T.R.™ NG333 Power Supply is used only with the 4-wire Qwik-BUS™ series intercom and/or video-intercom systems. The NG333 provides the regulated power needed to control the SP333 QwikBUS™ intelligent controller.

Each NG333 gets its power from a customer supplied power cord, and will operate on an input of 120VAC.

Each 4-wire QwikBUS™ system requires a minimum of one NG333 Power Supply.

FEATURES

- Easily Installs Right on Finished Wall Surface or in Optional Junction Box
- Operates on Safe Low-Voltage Class II Wiring
- Positive Screw Terminal and Plug-in Connectors

SPECIFICATIONS

Dimensions:	Height: 3.75" (96mm) Width: 4.25" (108mm) Depth: 2.375" (61mm) from mounting surface
Construction:	High impact Grey ABS plastic case
Connections:	Positive screw terminal and plug-in connectors
Temperature Range:	0-50 degrees C.
Mounting:	Surface-mounted (usually installed near the SP333 intelligent controller and other system central equipment).

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.