



### AM244A Panel Intercom/Call Module

The Alpha Communications® AM244A panel intercom/call modules are designed to be installed into the OF200 series panel frames. The AM244A modules are utilized in systems where communication is required to a resident location, when an emergency call is placed. The AM244A is typically used in conjunction with the CM800 (or equivalent) series emergency-call system(s).

The AM244A features an extruded aluminum module with two (2) high-impact ABS plastic speaker grilles, as well as a Tone-Off button, a Tone-Off Lamp and a Press to Talk button.

The AM244A requires a separate PK543A (or equivalent) amplifier, other than the one used for the concierge to apartment or entry intercom system. The AM244A can replace the CM800 tone speaker module from the emergency-call system.

#### FEATURES

- Extruded Aluminum Panel Module
- Momentary Pushbuttons for Tone-Off and Press to Talk functions
- Exceptional Voice and Tone Fidelity
- 'Simplex' Type Voice Communication
- Works with a Variety of Lobby Intercom Remote Stations
- Installs into Standard OF200 Series Panel Frames

#### SPECIFICATIONS

- Dimensions:** 4.00"W (102mm) x 15.25"H (387mm).
- Speakers:** Two (2) 3.50" (89mm) 45 ohm speakers, with one used for tone signal and one for voice intercom.
- Push-buttons:** Momentary pushbuttons for Tone-Off and Press To Talk voice intercom functions, as well as Red Tone-Off Lamp.

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*

#### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The panel intercom/call module(s) shall be Alpha Communications® AM244A, or approved equal. Module(s) shall be made of extruded aluminum in a natural anodized aluminum finish. Module shall fit into the standard OF200 series panel frame(s). The AM244A module(s) shall provide 'simplex' type voice communications. Module(s) shall have two (2) 3.5" (89mm) 45 ohm speakers (one for tone signal and one for voice intercom) and a momentary pushbutton for Tone-Off, a momentary pushbutton for Press-to-Talk, and a Red Tone-Off Lamp. Module shall be used with a separate PK543A amplifier (and any CM800 components needed and 16VAC transformer).

Contractor shall observe all local and national electrical and building codes.