



NC399P Alphanumeric Pager

ARCHITECTS' AND ENGINEERS' SPECIFICATION

Alphanumeric pager(s) shall be a Alpha Communications® NC399P Commtech Wireless 7900 or approved equal. It shall have a large 2 line display and shall be capable of storing up to 60 messages. The unit shall have a four (4) button design for ease of operation and shall provide a choice of tone and vibrating modes for page annunciation. A holster belt clip shall be provided with each unit.

The NC399P can be programmed to receive patient call information from Alpha Communications®/Tek-tone TC400 Nurse Call Systems via Alpha Communications® NC365A/AT Transmitter/Control Unit, as well as from Alpha Communications® NC300 or NC300II Nurse Call Systems. The alphanumeric patient call system shall be displayed as generated by the nurse call system and the pager shall generate annunciation either by sound or by vibration.

Copyright© 2009, Alpha Communications®, All Rights Reserved

NC399P Commtech 7900 Alphanumeric Pager

The NC399P Alphanumeric Pager is a radio pager receiver with a large 2 line display, and is designed for use with Alpha Communications® TC400 Nurse Call Systems as well as Alpha Communications® NC300 or NC300II (or other) Nurse Call and HC345C Emergency Call Systems. The NC399P will store up to 60 messages. Messages may be selectively deleted or locked into memory. Messages not locked into memory are automatically deleted as new messages arrive beyond the 60 message limit, with the oldest message being the first deleted. The NC399P can be configured for annunciation via vibration or audible tones, and has one alarm for daily annunciation. The NC399P can be programmed to turn on and off at preset times each day. Its CAP code may be reprogrammed in the field.

FEATURES

- Alphanumeric
- Two (2) line backlit display
- Easy to use large four (4) button design
- Configurable for audible or vibration alerts
- Field programmable
- Includes holster belt clip and safety cord

SPECIFICATIONS

Dimensions: Height: 1.90" (49mm)
(without belt clip)
Width: 2.70" (69mm)
Depth: 0.70" (18mm)

Construction: Electronic components surface mounted to PCB enclosed in an ABS plastic housing.

Operating Frequency: 457.550MHz

Operating Voltage: 1.5 vDC (1 AAA cell)
(batteries not included)

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.