



**MXA333 (Audio type)
QwikBUS™ Intelligent
Mixer Unit**

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The intelligent audio mixer(s) shall be Alpha Communications®/S.T.R.™ QwikBUS™ model MXA333, or approved equal. The MXA333 shall be built into a rugged high impact ABS plastic case, and shall be used with the associated SP333 intelligent controller (and associated SNT333 power supply) for up to 100 QwikBUS™ audio stations (25 per line maximum). Contractor shall furnish the proper number of MXA333 and SP333 units (and related components), depending upon system capacity.

Low voltage wiring shall be used and positive screw terminal and plug-in connectors shall be provided for installation wiring. The MXA333 shall be mountable right to the surface of the wall or in a customer-supplied junction box cabinet.

Contractor shall observe all local and national electrical and building codes.

Copyright© 2009-2011, Alpha Communications®, All Rights Reserved



MXA333 Audio Type Intelligent Mixer

The Alpha Communications®/S.T.R.™ MXA333 intelligent mixer is used only with the QwikBUS™ series intercom systems for systems with more than 100 addressable QwikBUS™ audio stations. The MXA333 provides the intelligent circuitry needed to install multiples of 100 QwikBUS™ stations, allowing systems with very large system capacities.

Each MXA333 gets its power from its associated SP333 intelligent controller and corresponding SNT333 power supply. All MXA333 field connections are positive screw terminal type, or plug-in type. Each MXA333 requires the SP333 and SNT333, and C333-2 connecting cable assembly.

FEATURES

- Easily Installs Right on Finished Wall Surface or in Optional Junction Box
- Operates on Safe Low-Voltage Class II Wiring
- Positive Screw Terminal Connectors

SPECIFICATIONS

<u>Dimensions:</u>	Height: 3.75" (96mm) Width: 4.25" (108mm) Depth: 2.375" (61mm) from mounting surface
<u>Construction:</u>	High impact Grey ABS plastic case
<u>Connections:</u>	Positive screw terminal connectors
<u>Temperature Range:</u>	0-50 degrees C.
<u>Mounting:</u>	Surface-mounted (usually installed near the system amplifier/power supply and other system central equipment).

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.