



SF113A

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Emergency Pushbutton Station(s) shall be Alpha Communications® SF113A, or approved equal and shall include a momentary (round) low voltage SPST pushbutton switch, and shall be marked "EMERGENCY" in Black lettering.

The station shall be mounted into a standard single gang electrical box (or ring). Two (2) screw terminals shall be provided for connections. Faceplate shall be flame retardant White ABS plastic (with mounting screws provided).

Contractor shall observe all local and national electrical and building codes.

SF113A Emergency Pushbutton Station

The Alpha Communications® model SF113A Emergency Pushbutton Station includes a momentary (round) low voltage SPST pushbutton switch.

The SF113A can be used as an indoor emergency contact device or pushbutton for a variety of systems.

The SF113A features a flame retardant type White ABS plastic faceplate marked "EMERGENCY" in Black lettering, and mounts on a single gang electric box or plaster ring.

FEATURES

- White Plastic flame retardant ABS Faceplate
- Momentary (round) low voltage SPST pushbutton switch

SPECIFICATIONS

Dimensions: Height: 4.50" (114mm)
Width: 2.75" (70mm)
Depth: 0.50" (13mm) (into wall)

Faceplate: Flame retardant White ABS plastic.

Marking: "EMERGENCY" in Black Letters

Mounting: Steel City #52171 box with Steel City #52C14 plaster ring, or Alpha Communications® Model #IH358 box with IH357 ring, or EXACT EQUAL. Vertical mount.

Construction: White flame retardant ABS plastic faceplate.

Connections: Two (2) Screw Terminals.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.