



# Product Specification Sheet



APS709

Rev. 3 - 09/2009



**NC317PPC Panel PC with 17.0" Touchscreen Monitor**

## ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The Panel PC with 17.0" 300 NIT 5-wire Resistive type Touchscreen Monitor(s) shall be Alpha Communications® AlphaEntry™ model NC317PPC, or approved equal. The NC317PPC shall include Genuine Windows XP® embedded OS with an Intel® Celeron® M Processor. The NC317PPC shall feature a 70GB slim hard drive, 4 USB 2.0 ports and integrated audio - stereo speakers. Unit shall be finished in the standard Black finish (or optional extra cost finish as directed by the building owner or architect/designer). Unit shall be mounted to the surface of the finished wall using an optional VESA (100mm) mounting bracket, or shall be mounted behind a decorative faceplate (finish, type and size as directed by the building owner or architect/designer).

Contractor shall observe all local and national electrical and building codes.



## NC317PPC Panel PC with 17" Touchscreen Monitor

The Alpha Communications® NC317PPC Panel PC with 17" Touchscreen Monitor is used primarily with the AlphaEntry™ software to act as a Concierge or Master Station for calling to and from remote communication devices, but can also be used for other system and software applications.

The NC317PPC is an all-in-one computer that fits both the PC and monitor into a stunning, space-saving design. The NC317PPC can be mounted as is on the wall surface using a standard VESA type mounting bracket (not included) or the NC317PPC can be custom built into a lobby station faceplate by us, in a variety of finishes and dimensions.

A large 17.0" LCD touchscreen make it ideal for displaying a large amount of data onscreen, and enabling the user to choose from keyboard or touchscreen functionality.

### FEATURES

- Genuine Windows XP® Embedded OS with Intel® Celeron® M 1.5Ghz processor
- 2GB Dual Channel DDR SDRAM at 400MHz
- Keyboard option
- 70GB slim 2.50" Hard Drive
- Vandal-resistant and Dust/Water-resistant front, sealed IP55 / Nema 3
- Integrated 17.0" (measured diagonally) Long-Life LCD (1280x1024) Touchscreen 5-wire Resistive Type (50,000 MTBF hours) 300 NIT brightness
- Abundant I/O including 4 Integrated USB 2.0 Ports
- Integrated Audio - Stereo Speakers
- 19VDC 90W plug-in Power Supply Included
- Small footprint space saving design
- Standard Black or optional St. Steel finish
- Other options available at optional extra cost
- Optional WiFi (model# NC317PPCWF)
- Operating Temperature 0°C ~ 40°C (32°F ~ 104°F)

**Outside Dimensions:** 16.20"w x 13.60"h x 3.0"d (less any mounting bracket or housing).

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*