



Product Specification Sheet



APS714

Rev. 1 - 10/2009



**CB-4200
Area of Rescue Cable**

4200 Series Area of Rescue Plenum Cable

Alpha Communications®/Cornell CB-4200 Area of Rescue plenum cable is specifically designed to work with the 4200 Seriea Area of Rescue system(s). The cable is home-run from the 4200 series master station to each corresponding remote station. The CB-4200 cable is U.L. and cU.L. Listed and may be used as a Plenum type cable in CL3P or CMP applications. The CB-4200 cable is only sold in an easy-reel box of 1,000 feet (+/-5%).

SPECIFICATIONS

- Description:** #18AWG, 4 Conductor Bare Copper with #22AWG 1 Pair Shielded Bare Copper Plenum CL3P / CMP
- Conductor Description:** #18AWG (7/26 Bare Copper) #22AWG (7/30 Bare Copper)
- Color Code:** #18AWG Brown / Grey / Green / Red and #22AWG Black / White
- Shielding:** #22 Pair Only - Aluminum Mylar
- Drain Wire:** #24AWG 7 Strand Tinned Copper
- Insulation:** Low-Smoke PVC .008"
- Jacket:** Low-Smoke PVC .018"
- Overall Diameter:** .274" Nominal
- Temperature and Voltage Rating:** 75C / 300 Volt
- Length:** 1,000 feet +/-5%

Flame Rating
Approved For Plenum Use Without Conduit per NEC

Article 800 by Passing UL-910 Steiner Tunnel Test

Agencies Approvals
NEC Article 800, 725; UL CL3P/CMP, (UL)



Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.

Copyright© 2009, Alpha Communications®, All Rights Reserved