



Product Specification Sheet



APS726

Rev. 1 - 12/2009



SF515ES Wireless Passive Infra-Red Detector

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The wireless Passive Infra-Red Detector(s) shall be Alpha Communications®/TekTone SF515ES or approved equal. It shall use the 900 MHz frequency for signal transmission. The SF515ES's opaque Fresnel lens shall focus infrared energy on pyroelectric sensors, reducing false alarms caused by stray light or heat sources.

No physical wiring connections shall be required to transmit an alarm call. The SF515ES shall be powered by a 3V lithium battery. Mounting hardware and housing shall permit flat wall, corner or hallway mounting, with swivel adjustments for aiming for nominal coverage. The transmitter shall be no larger than 2.875" w x 3.688" h x 2.063" d.

TekTone® has designed the Tek-CARE®500 to work as a system. Its NC501ES Master Station Computer has been carefully designed and matched to work with Tek-CARE®500 wireless and wired peripherals. TekTone® will not warrant or support components of Tek-CARE®500 that are purchased separately unless the components are add-ons to previously sold systems. TekTone® will also not warrant or support a system that is a mix of TekTone® and Non-TekTone® parts, unless prior written permission has been obtained. In order to track our systems and to inform facilities of software upgrades, full site information (site name, address and phone number) will be required when ordering. Site information and NC501ES warranty number will also be required when requesting technical support.

Copyright© 2009, Alpha Communications®, All Rights Reserved

SF515ES Wireless Passive Infra-Red Detector

The Alpha Communications® SF515ES Wireless Passive Infra-Red Detector is for use with the Tek-CARE®500 Wireless Emergency Call System. The detector features advanced digital signal processing to recognize "human signature" size and movement, reducing false alarms. The SF515ES has a tamper-protected case and the 3V lithium battery is included.

The SF515ES Wireless Passive Infra-Red Detector is ideal for residential and low-traffic commercial applications. With GEInterlogix's 'premier Sharpshooter™', the SF515ES has increased immunity to radio interference, vibration, static, stray light, rapid temperature changes and other false alarm sources. It provides 90° x 45' coverage.

FEATURES

- Reliable 900MHz frequency EchoStream® operation
- Dual pyroelectric sensors
- Sequence processor with bi-directional pulse counting and event verification
- Flat wall, corner or hallway mounting, with swivel adjustments
- Fire-retardant antique white ABS plastic housing

SPECIFICATIONS

<u>Dimensions:</u>	Height: 3.688" (94mm)
	Width: 2.875" (74mm)
	Depth: 2.063" (53mm)
<u>Coverage Area:</u>	45' x 90°
<u>Power:</u>	Two (3) 3V Lithium batteries (included)
<u>Battery Life:</u>	2 years (32°F-120°F)
<u>Environment:</u>	12°C-49°C (10°F-120°F); 10% to 90% non-condensing relative humidity
<u>Swivel:</u>	± 10° right or left, 15° down
<u>Battery:</u>	3V Lithium (model # BA505)

REQUIRED COMPONENTS

Tek-CARE500 Wireless Emergency Call System

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.