



**D6L-PLUS/2H
6-Output
Video Distributor Unit
(shown without plastic cover)**

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The 6-Output Video Distributor Unit(s) shall be Alpha Communications®/Golmar model D6L-PLUS/2H, or approved equal. The D6L-PLUS/2H shall be built into a rugged high impact ABS plastic case and shall provide 6 isolated and amplified twisted pair video outputs. Contractor shall furnish the proper number of D6L-PLUS/2H units, depending upon system capacity.

Low voltage wiring shall be used and positive screw terminal connectors shall be provided for installation wiring. The D6L-PLUS/2H shall be mountable right to the surface of the wall or in a customer-supplied junction box cabinet.

Contractor shall observe all local and national electrical and building codes.

Copyright© 2010, Alpha Communications®, All Rights Reserved

D6L-PLUS/2H 6-Output Video Distributor Unit

The Alpha Communications®/Golmar D6L-PLUS/2H 6-output Video Distributor unit is used only with the Golmar intercom and/or video-intercom systems. The D6L-PLUS/2H provides 6 isolated and amplified twisted pair video outputs to feed up to 6 risers (lines), and additional D6L-PLUS/2H units.

All D6L-PLUS/2H field connections are positive screw terminal type.

FEATURES

- Easily Installs Right on Finished Wall Surface or in Optional Junction Box
- Positive Screw Terminal Connectors

SPECIFICATIONS

Dimensions:	Height: 2.36" (60mm) Width: 3.43" (88mm) Depth: 1.15" (30mm) from mounting surface
Construction:	High impact Grey ABS plastic case
Connections:	Positive screw terminal connectors
Mounting:	Surface-mounted (usually installed near the system amplifier/power supply and other system central equipment).

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.