



**TAK-4208 Telephone
Auto Dialer Unit**

**ARCHITECTS' AND ENGINEERS'
SPECIFICATIONS**

The Telephone Auto Dialer Unit unit(s) shall be Alpha Communications®/Cornell model TAK-4208, or approved equal. The TAK-4208 shall be used in conjunction with an Alpha Communications® Emergency-Call (or similar) notification system, for up to eight (8) inputs.

The TAK-4208 shall be a fully programmable auto dialer and digital announcer, designed for message notification. Once a contact input is detected, the TAK-4208 shall dial up to eight (8) phone numbers and play a pre-recorded message of up to one (1) minute in length.

Low voltage wiring shall be used and positive screw terminal and plug-in connectors shall be provided for installation wiring. The TAK-4208 shall be mountable right to the surface of the wall or in a customer-supplied junction box cabinet, and shall require a customer supplied external phone line and jack.

Contractor shall observe all local and national electrical and building codes.

**TAK-4208 Telephone
Auto Dialer Unit**

The Alpha Communications®/Cornell TAK-4208 is a fully programmable auto dialer and digital announcer, designed for message notification. Once an alarm contact is actuated, the TAK-4208 can dial up to eight (8) phone numbers and play a pre-recorded message up to one (1) minute in length.

Messages can be recorded locally or remotely. When configured as an alarm dialer, the TAK-4208 has call progress detection capability with normal and fast busy, call pickup, CPC, and ring-to-answer detection.

Programming can be done with a touch tone phone, or by using a PC with a serial port connection and the supplied software. The TAK-4208 comes with the required 12VDC plug-in power supply, and has up to eight (8) inputs.

FEATURES

- Easily Installs Right on Finished Wall Surface or in Optional Junction Box
- Operates on Safe Low-Voltage Class II Wiring
- Positive Screw Terminal and Plug-in Connectors
- Works with a variety of alarm notification equipment
- Easily programs with a touch tone phone or PC

SPECIFICATIONS

<u>Dimensions:</u>	Height: 6.30" (161mm)
	Width: 8.30" (211mm)
	Depth: 1.80" (46mm) from mounting surface
<u>Construction:</u>	Black painted metal case
<u>Connections:</u>	Positive screw terminal and plug-in connectors
<u>Mounting:</u>	Surface-mounted (usually installed near the other system central equipment).

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.