



# Product Specification Sheet

APS794  
Rev. 1 - 02/2011



**LI386LED**  
**4- Color LED - Addressable**  
**Corridor Dome/Zone Light**  
**(shown with all 4 sections lighted)**

## ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

Addressable corridor dome/zone light(s) shall be Alpha Communications®/TekTone model LI386LED or approved equal. The corridor light shall be sectional in design. Lights shall include LEDs to provide WHITE, RED, AMBER/YELLOW, and GREEN annunciation through a translucent plastic lens. All lenses shall be mounted on a FOG-WHITE flame retardant (UL® 94HB) plastic base panel. The four (4) colored LEDs shall indicate patient call priority and staff presence. Data signals from the dome/zone light shall be supervised to the central equipment (CE). The unit shall provide visual and digital communications to and from the CE. The LI386LED shall be a standalone unit that connects directly to the CE.

LI386LED shall be U.L. 1069 listed, when used with the corresponding U.L. 1069 nurse-call system.

Contractor shall observe all local and national electrical and building codes.

## LI386LED 4-Color LED Addressable Corridor Dome/Zone Light

The Alpha Communications® LI386LED 4-color LED corridor dome light with built-in multipurpose station provides visual indication of calls originating from bath, emergency, and code call stations, when used as a dome light. The LI386LED indicates calls originating from patient and staff stations when used as a zone light. The LI386LED also indicates calls from the zones to which those stations are assigned and provides communication to and from the central equipment (CE), including the nurse master station and monitor. No controls are provided.

### FEATURES

- UL 1069 Listed
- Long lasting LEDs - No bulb replacements
- Plug-in connector supplied
- Excellent visibility
- Attractive flame-retardant plastic panel
- Addressable station with data signal supervision
- Simplified multiplex wiring

### SPECIFICATIONS

<b>Dimensions:</b>	Height: 4.80" (122mm)
(overall)	Width: 5.00" (127mm)
	Depth: 2.755" (70mm)
	from finished wall surface
<b>Power</b>	24VDC
<b>LEDs:</b>	2VDC, 20mA
<b>Finish:</b>	<b>Base:</b> FOG WHITE flame retardant (UL® 94HB) plastic
	<b>Lens:</b> Flame retardant translucent polycarbonate plastic
<b>Mounting:</b>	Fits standard one or two gang electrical box with one or two gang plaster ring.

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*