



**IS204 'Universal' 4-wire
Apartment Intercom Station**

**ARCHITECTS' AND ENGINEERS'
SPECIFICATIONS**

Universal' apartment stations shall be Alpha Communications® model IS204 or approved equal, equipped with momentary action push-buttons for TALK, LISTEN, and DOOR operation. Each push-button shall have both English and Universal Graphic Symbol imprinting, as well as Braille lettering. The mylar cone speaker/microphone shall be a 2.5" high-sensitivity type with voice-frequency response. Screw terminal connections shall be provided for positive wiring termination, and shall allow for connection to popular 4-wire intercom system configurations. The station shall be molded of high-impact, flame retardant ABS plastic, in a white finish.

The IS204 shall be supplied with 2 vertical and 2 horizontal mounting holes, to allow surface mounting over a single-gang electrical box or mounting ring, or over the popular IH101 and/or IH102 flush housing(s). Four (4) mounting hole plugs shall be provided for covering the four (4) mounting holes and two (2) mounting screws (provided).

Contractor shall observe all local and national electrical and building codes.

Copyright© 2011, Alpha Communications®, All Rights Reserved

**IS204 'Universal'
Apartment Intercom Station**

The Alpha Communications® IS204 is a universal 4-wire apartment intercom station which combines modern styling with ease of operation to provide natural, clear voice communication and positive door-release operation. The white, high-impact, ABS plastic faceplate blends with any decor. The advanced circuitry and versatility permits use in large or small buildings, with one or several entrances.

The 2 vertical and 2 horizontal mounting holes allow the IS204 to mount over a single-gang electrical back box (or mounting ring) or over the IH101 and/or IH102 flush housing(s). This unit replaces at least 2 models of existing intercom stations! With the addition of the optional model AP543 adaptor plate, you can now replace 4 existing stations.

A wide variety of optional accessories is available to provide additional functions such as multiple entrance operation, post office door release, etc.

FEATURES

- Surface mounting or mounts over flush housing
- Simple, push button operation
- Easy installation
- Unique design allows vertical or horizontal screw mounting
- Clear voice-quality
- Precision-engineered for reliability
- English and international (graphic) symbols
- Braille lettering on faceplate

SPECIFICATIONS

Dimensions:	Height: 7.00" (178mm)
	Width: 5.00" (127mm)
	Projects: 1.00" (26mm) from mounting surface
Finish:	Durable, high-impact ABS plastic.
Controls:	Individually replaceable type push buttons with self-wiping contacts. Identified for TALK, LISTEN, and DOOR functions.
Speaker/Mic:	2.50" (62.5mm) mylar cone with voice response. Also used for electronic tone signal.
Connection	Screw terminals standard.
Housing:	Surface mounts over single gang electrical box or mounting ring, or right on the wall, or over the IH101 and/or IH102 flush housing(s)

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.