



**RS101S (shown with red  
Call-Placed light illuminated)**

### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

Remote tone sounder station(s) shall be Alpha Communications® model RS101S or approved equal.

The RS101S stations shall include a built-in Tone Speaker mounted behind a rugged 2mm thick Natural Anodized Aluminum faceplate. The RS101S shall be also include an internal Red Tone Lamp and double-contact momentary Tone-Off pushbutton.

RS101S tone sounder stations shall provide remote audible and visual annunciator when used in conjunction with Alpha Communications® AlphaEcall™ 100 series annunciator and AC219 Control Unit, or similar system.

The RS101S shall protrude from the finished wall surface a maximum of 1.3875" (35mm), and shall be only 3.25" wide (83mm).

Contractor shall observe all local and national electrical and building codes.

### RS101S Remote Tone Sounder Station

The RS101S remote tone sounder stations provide for remote audible and visual annunciation when connected directly in parallel with an Alpha Communications® AlphaEcall™ 100 series annunciator and AC219 control unit, or CM800 or DS100 series annunciator and PK2019 control unit. The RS101S stations feature a momentary contact Tone-Off button for tone silencing. Depressing the Tone-Off button silences the tone at all sounding locations. When the emergency initiating device has been reset, the Tone-Off will automatically reset. The RS101S also includes a red Call-Placed light which will illuminate when an initial call is placed on the Alpha Communications® AlphaEcall™ 100 series system.

### FEATURES

- Easy installation - fully surface mount
- Red Call-Placed light (concealed)
- Pushbutton Tone-Off reset
- Reliable and rugged 2mm thick Aluminum faceplate
- Advanced design

### SPECIFICATIONS

<b>Dimensions:</b>	Height: 6.875" (175mm) Width: 3.25" (83mm) Width: 1.375" (35mm) at it's deepest point on the surface housing
<b>Finish:</b>	Natural Anodized Aluminum faceplate
<b>Controls:</b>	Individually replaceable push button with self-wiping double contacts
<b>Indicator:</b>	28 volt red light (concealed)
<b>Tone Speaker:</b>	50-ohms, Round (50mm)
<b>Connections:</b>	Pigtails
<b>Housing:</b>	Hi-impact plastic, surface mount housing included

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*